## MLLG-E-LED-EXPLD-150-50-[V]-C1D1

150 Watt Square Explosion Proof LED Light

Project Name



#### **DETAILS**

Our D Series is a square Class 1 Division 1 (C1D1) explosion proof LED fixture. It comes standard with a 3/4 pendant mount and a surface mount trunnion. Ideal for any hazardous locations where flammable materials are present. Available in both 120-277v and 277-480v.

OVER\	VIEW LG-E-LED-EXPLD-150-50-[V]-C1D1
Watts	150
Lumens	21000
Lumens Per Watt (Efficacy)	140
Color Temperature	5000K
Voltage	100V-277V   277V-480V



### **▶** PRODUCT DIMENSIONS

Product Dimensions	15.7 X 11.2 X 9.96 in
Product Weight	26.9 lbs



♥ UL SPECS
JL 844 Hazardous Locations
Class I, Division 1, Groups C,D
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III
JL 1598 Suitable for Wet Locations
JL 1598A Marine Outside Type
ABS



# MLLG-E-LED-EXPLD-150-50-[V]-C1D1

150 Watt Square Explosion Proof LED Light

Project Name



WebID: 1282

PRODUCT SPECIFICATIONS		
	Watts	150
	Lumens	21000
	Color Temperature	5000K
	CRI	70+
	Replaces	400 Watt Metal Halide
	Voltage	100-277   277-480
	Power Factor (PF)	>.95
	THD	< 10%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	IP Rating	IP66
	IK Rating	IK10
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible   ETL Listed   ROHS
	Warranty	5
	Mount	Yoke
	Color Options	Gray



# MLLG-E-LED-EXPLD-150-50-[V]-C1D1

150 Watt Square Explosion Proof LED Light

Project Name



WebID: 1282

### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	150	\$141.70	\$708.50

## **PRODUCT FAMILY MODELS**

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLD-60-50-C1D1	60	8100	135
MLLG-E-LED-EXPLD-80-50-[V]-C1D1	80	11200	140
MLLG-E-LED-EXPLD-100-50-[V]-C1D1	100	14000	140
MLLG-E-LED-EXPLD-150-50-[V]-C1D1	150	21000	140

