MLLG-E-LED-EXPLI-80-50-[V]-C1D1

80 Watt Explosion Proof Linear LED Light

Project Name _____



DETAILS

80 Watt LED Explosion Proof fixture - Class 1 Division 1. These lights are a compact linear fixture that replaces fluorescent lighting and metal halide lighting. This is a die-cast aluminum fixture designed for industrial hazardous locations. Extremely robust with high impact IK10 and wet weather rating IP66 for both indoor and outdoor applications.

UVERVIEW			
SKU	MLLG-E-LED-EXPLI-80-50-[V]- C1D1		
Watts	80		
Lumens	11200		
Lumens Per Watt (Efficacy)	140		
Onlan Tanananahana	50001/		



Voltage 100V-277V | 277V-480V



∠[¬] PRODUCT DIMENSIONS

Product Weight 26 lbs



UL 844 Hazardous Locations

Class I, Division 1, Groups C,D

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations

UL 1598A Marine Outside Type

ABS





MLLG-E-LED-EXPLI-80-50-[V]-C1D1

80 Watt Explosion Proof Linear LED Light

Project Name _____



PRODUCT SPECIFICATIONS				
OPTICAL	Watts	80		
	Lumens	11200		
	Color Temperature	5000K		
	CRI	70+		
	Replaces	250 Watt Metal Halide		
ELECTRICAL	Voltage	100-277 277-480		
	Power Factor (PF)	>.95		
	THD	< 10%		
Dimming		1-10V		
	Power Factor (PF)	50-60Hz		
CONSTRUCTION	IP Rating	IP66		
IK Rating Rated Life		IK10		
		50,000 (L70) hours		
	Certifications	Rebate Eligible ETL Listed NSF Certified ROHS CB		
	Warranty	5		
	Mount	Yoke 3/4 in NPT Pendant		
	Color Options	Gray		



MLLG-E-LED-EXPLI-80-50-[V]-C1D1

80 Watt Explosion Proof Linear LED Light

Project Name _____



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	80	\$96.36	\$481.78

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLI2-50-50-U-C1D1	50	7000	140
MLLG-E-LED-EXPLI-40-50-[V]-C1D1	40	5600	140
MLLG-E-LED-EXPLI-60-50-[V]-C1D1	60	8400	140
MLLG-E-LED-EXPLI-80-50-[V]-C1D1	80	11200	140
MLLG-E-LED-EXPLI-100-50-[V]-C1D1	100	14000	140

4 SAMPLE COMPLETED PROJECTS WITH THIS PRODUCT





