MLLG-LED-WPFL-60-50-PC

60 Watt LED Wall Pack

Project Name



DETAILS

60 Watt LED flood wall pack has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate lens. Excellent impact, corrosion, and UV resistance with the dark bronze polyester powder finish. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. This fixture is equipped with a photocell.



Photocell

OVERVIEW		
SKU	MLLG-LED-WPFL-60-50-PC	
Wattage	60	
Lumens	7928	
Lumens Per Watt (Efficacy)	132	
Color Temperature	5000K	
Voltage	100V-277V	



Product Dimensions	13.1 in L X 9.5 in W X 7.5 in H
Product Weight	8 lbs



Wattage	Current Amp Draw			
Wattage	120V	240V	277V	480V
60	0.50	0.25	0.22	0.13













 $Product\ design\ upgrades\ may\ result\ in\ specification\ changes\ without\ notice.\ Speak\ to\ a\ Product\ Specialist\ for\ the\ latest\ information.$

MLLG-LED-WPFL-60-50-PC

60 Watt LED Wall Pack

Project Name



PRODUCT SPECIFICATIONS		
	Wattage	60
	Lumens	7928
	Color Temperature	5000K
	CRI	75+
	Beam Angles	120°
	Replaces	200 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	> .90
	THD	< 20%
	Dimming	No
	Power Factor (PF)	50-60Hz
	Housing	Powder Coated Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-40°F to +122°F
	Rated Life	50,000 hours
	Certifications	Rebate Eligible UL Listed ROHS
	Warranty	5
	Mount	Wall
	Color Options	Bronze



MLLG-LED-WPFL-60-50-PC

60 Watt LED Wall Pack

Proie	ct Name	



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
200	60	\$79.35	\$396.76

PRODUCT FAMILY MODELS

SKU	Wattage	Lumens	Lumens/Watt
MLLG-LED-WPFL-40-50-PC	40	5300	133
MLLG-LED-WPFL-60-50-PC	60	7928	132
MLLG-LED-WPFL-80-50-PC	80	11065	138

♦ SAMPLE COMPLETED PROJECTS WITH TTHIS PRODUCT





