## MLLG-LED-WPFL-80-50-PC

80 Watt LED Wall Pack

Project Name



#### **DETAILS**

80 Watt LED flood wall pack has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate lens. Excellent impact, corrosion, and UV resistance with the dark bronze polyester powder finish. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. This fixture is equipped with a photocell.



Photocell

OVERVIEW		
SKU	MLLG-LED-WPFL-80-50-PC	
Wattage	80	
Lumens	11065	
Lumens Per Watt (Efficacy)	138	
Color Temperature	4000K   5000K	
Voltage	100V-277V	



Product Dimensions	13.1 X 9.5 X 7.5 in
Product Weight	8 lbs



Wattage	Current Amp Draw			
	120V	240V	277V	480V
80	0.67	0.33	0.29	0.17















Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

# MLLG-LED-WPFL-80-50-PC

80 Watt LED Wall Pack

Project Name



PRODUCT SPECIFICATIONS		
	Wattage	80
	Lumens	11065
	Color Temperature	4000K   5000K
	CRI	75+
	Beam Angles	120°
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	> .90
	THD	< 20%
	Dimming	No
	Power Factor (PF)	50-60Hz
	Housing	Powder Coated Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-40°F to +122°F
	Rated Life	50,000 hours
	Certifications	Rebate Eligible   UL Listed   ROHS
	Warranty	5
	Mount	Wall
	Color Options	Bronze



# MLLG-LED-WPFL-80-50-PC

80 Watt LED Wall Pack

Project Name



### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
250	80	\$96.36	\$481.78

### **PRODUCT FAMILY MODELS**

SKU	Wattage	Lumens	Lumens/Watt
MLLG-LED-WPFL-40-50-PC	40	5300	133
MLLG-LED-WPFL-60-50-PC	60	7928	132
MLLG-LED-WPFL-80-50-PC	80	11065	138

## **♦ SAMPLE COMPLETED PROJECTS WITH TTHIS PRODUCT**



