### MLLG-HD-LED-HM-320-[Color]-[V]

320 Watt LED High Mast Light

Project Name



#### **DETAILS**

Our high mast lights have a die-cast aluminum housing and polyester paint finish with a 5,000-hour salt fog rating. Prismatic glass optics provide high application efficacy, uniformity, and glare control. Specialized high mast optics ensure wide distributions to maximize light distribution for multiple pole installation. 3G vibration rated. 3/5/7-pin photocell control available. The fixture has an adjustable angle mount 2 3/8" O.D. tenon. 4-bolt mounting and safety cables ensure the fixture is locked onto the pole.



Photocell

OVERVIEW			
SKU	MLLG-HD-LED-HM-320-[Color]-[V		
Wattage	320		
Lumens	44800		
Lumens Per Watt (Efficacy)	140		
Color Temperature	4000K   5000K		
Voltage	100V-277V   277V-480V		



**Product Dimensions** 

Product Weight 48 lbs



SKU	Voltage
MLLG-HD-LED-HM-320-50	100V-277V
MLLG-HD-LED-HM-320-50-HV [T]	277V-480V



















Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

# MLLG-HD-LED-HM-320-[Color]-[V]

320 Watt LED High Mast Light

Project Name



PRODUCT SPECIFICATIONS			
	Wattage	320	
	Lumens	44800	
	Color Temperature	4000K   5000K	
	CRI	70+	
	Beam Angles	Type 2,3,4,5	
	Replaces	1000 Watt Metal Halide	
	Voltage	100-277   277-480	
	Power Factor (PF)	> .90	
	THD	< 20%	
Dimming Surge Protection Power Factor (PF) Housing IP Rating		1-10V   Optional	
		10 kVa or 20 kVa	
		50-60Hz	
		Aluminum Alloy and PC Lens	
		IP66	
	IK Rating	IK08	
	Operating Temperature	-40°F to +140°F	
	Rated Life	100,000 (L70) hours	
	Certifications	Rebate Eligible   UL Listed   ROHS   CB	
	Warranty	5	
	Mount	Pole	



## MLLG-HD-LED-HM-320-[Color]-[V]

320 Watt LED High Mast Light

Project Name



#### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
1000	320	\$385.42	\$1,927.12

### **PRODUCT FAMILY MODELS**

SKU	Wattage	Lumens	Lumens/Watt
MLLG-WD-LED-BARN-45-50	45	6300	140
MLLG-AG-LED-IMF-600-5-[Optic]-TR-[V]	600	84000	140

### AMP DRAW

Mattaga		Current Amp Draw		
Wattage	120V	240V	277V	480V
320	2.67	1.33	1.16	0.67

