MLLG-LN-LED-CANR-60-50-[MS]

30 / 40 / 60 Watt Adjustable Canopy Light

Project Name



DETAILS

The 30 | 40 | 60 wattage adjustable LED canopy fixture is designed with die-cast aluminum heat sink housing and finished with an anti-corrosion white powder coat. Lens is tough vandal-proof clear acrylic. The fixture is surface-mounted and has 1/2 inch coin plugs for easy conduit access. Optional Integrated Motion Sensor is available on this fixture.



No Motion Sensor



Motion Sensor

OVERVIEW		
SKU	MLLG-LN-LED-CANR-60-50-[MS]	
Wattage	30 40 60	
Lumens	3900 5200 7800	
Lumens Per Watt (Efficacy)	130	
Color Temperature	5000K	
Voltage	100V-277V	







Features
No Motion Sensor
Motion Sensor











WebID: 1563



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

MLLG-LN-LED-CANR-60-50-[MS]

30 / 40 / 60 Watt Adjustable Canopy Light

Project Name



WebID: 1563

PRODUCT SPECIFICATIONS		
	Wattage	30 40 60
	Lumens	3900 5200 7800
	Color Temperature	5000K
	CRI	70+
	Beam Angles	130°
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	>.90
	THD	< 20%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	Housing	Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-40°F to +113°F
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible UL Listed ROHS
	Warranty	5
	Mount	Pendant Surface
	Color Options	White



MLLG-LN-LED-CANR-60-50-[MS]

30 / 40 / 60 Watt Adjustable Canopy Light

Project Name



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
250	30	\$124.70	\$623.48
250	40	\$119.03	\$595.14
250	60	\$107.69	\$538.46

AMP DRAW

Wattaga		Current Amp Draw		
Wattage	120V	240V	277V	480V
30	0.25	0.13	0.11	0.06
40	0.33	0.17	0.14	0.08
60	0.50	0.25	0.22	0.13

