MLLG-E-LED-EXPLH-40-50-[V]-C1D2

40 Watt Explosion Proof Linear LED Light

Project Name



DETAILS

SKU

Our Linear H Series C1D2 Explosion Proof fixtures come in both 120-277v and 277-480v configurations. At 140 lumens per watt they are an efficient and safe replacement solution for environments where ignitable gases or vapors may be present in the air under abnormal

OTENTEN
MLLG-E-LED-EXPLH-40-50-[V]- C1D2

Watts 40 Lumens 5600

NVFRVIFW

Lumens Per Watt (Efficacy) 140

5000K **Color Temperature**

100V-277V | 277V-480V Voltage

PRODUCT DIMENSIONS

Product Weight 20 lbs

UL SPECS

UL 844 Hazardous Locations

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations


UL 1598A Marine Outside Type

ABS













MLLG-E-LED-EXPLH-40-50-[V]-C1D2

40 Watt Explosion Proof Linear LED Light

Project Name _____



PRODUCT SPECIFICATIONS					
OPTICAL	Watts	40			
	Lumens	5600			
	Color Temperature	5000K			
	CRI	70+			
	Replaces	175 Watt Metal Halide 250 Watt Metal Halide			
ELECTRICAL	Voltage	100-277 277-480			
	Power Factor (PF)	>.95			
	THD	< 10%			
	Dimming	1-10V			
	Power Factor (PF)	50-60Hz			
CONSTRUCTION	IP Rating	IP66			
	IK Rating	IK10			
	Rated Life	50,000 (L70) hours			
	Certifications	Rebate Eligible ETL Listed NSF Certified ROHS CB			
	Warranty	5			
	Mount	Bracket Surface Wall 3/4 in NPT Pendant			
	Color Options	Gray			



MLLG-E-LED-EXPLH-40-50-[V]-C1D2

40 Watt Explosion Proof Linear LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	40	\$119.03	\$595.14

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLH-40-50-[V]-C1D2	40	5600	140
MLLG-E-LED-EXPLH-60-50-C1D2	60	8400	140

