MLLG-E-LED-EXPLH-60-50-C1D2

60 Watt Explosion Proof Linear LED Light

Project Name _____



DETAILS

Our Linear H Series C1D2 Explosion Proof fixtures come in both 120-277v and 277-480v configurations. At 140 lumens per watt they are an efficient and safe replacement solution for environments where ignitable gases or vapors may be present in the air under abnormal conditions.

OVERVIEW			
SKU	MLLG-E-LED-EXPLH-60-50-C1D2		
Watts	60		
Lumens	8400		
Lumens Per Watt (Efficacy)	140		
Color Temperature	5000K		
Voltage	100V-277V 277V-480V		



Product Weight 20 lbs

UL SPECS

UL 844 Hazardous Locations

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations


UL 1598A Marine Outside Type

ABS











MLLG-E-LED-EXPLH-60-50-C1D2

60 Watt Explosion Proof Linear LED Light

Project Name _____



PRODUCT SPECIFICATIONS				
OPTICAL	Watts	60		
	Lumens	8400		
	Color Temperature	5000K		
	CRI	70+		
	Replaces	250 Watt Metal Halide		
ELECTRICAL	Voltage	100-277 277-480		
	Power Factor (PF)	>.95		
	THD	< 10%		
Dimmin		1-10V		
	Power Factor (PF)	50-60Hz		
CONSTRUCTION	IP Rating	IP66		
	IK Rating	IK10		
Rated Life		50,000 (L70) hours		
	Certifications	Rebate Eligible ETL Listed NSF Certified ROHS CB		
	Warranty	5		
	Mount	Bracket Surface Wall 3/4 in NPT Pendant		
	Color Options	Gray		



MLLG-E-LED-EXPLH-60-50-C1D2

60 Watt Explosion Proof Linear LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	60	\$107.69	\$538.46

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLH-40-50-[V]-C1D2	40	5600	140
MLLG-E-LED-EXPLH-60-50-C1D2	60	8400	140

