MLLG-AL-LED-CAN12MV-20-CC-NK

20 Watt 12 In LED Flush Mounted Ceiling Light

Project Name



DETAILS

Flush-mounted LED ceiling lights are lighting fixtures designed to be installed directly on a ceiling surface. Our fixtures offer bright, efficient lighting for commercial, industrial, and even residential applications. Unlike recessed lighting, flush mounts do not require a cavity in the ceiling. They are perfect for low ceilings. Our flush-mounted LED lights come in a round shape and are offered in various sizes. They are available in different color temperatures, wattages, and lumen outputs. These fixtures are commonly used in offices, hallways, classrooms, storage rooms, and retail spaces.



Color Adjustable

OVERVIEW MITG-AL-LED-CAN12MV-20-CC-NK	
Watts	20
Lumens	1400
Lumens Per Watt (Efficacy)	70
Color Temperature	3000K 4000K 5000K
Voltage	100V-277V



Product Dimensions	12 in round
Product Weight	2 lbs



Watta		Current An	np Draw	
Watts	120V	240V	277V	480V
20	0.17	0.08	0.07	0.04



















MLLG-AL-LED-CAN12MV-20-CC-NK

20 Watt 12 In LED Flush Mounted Ceiling Light

Project Name



WebID: 1636

PRODUCT SPECIFICATIONS		
	Watts	20
	Lumens	1400
	Color Temperature	3000K 4000K 5000K
	CRI	80+
	Replaces	75W Incandescent
	Voltage	100-277
	Dimming	Triac
	Power Factor (PF)	50 / 60 hz
	Rated Life	50,000 hours
	Certifications	Energy Star Rebate Eligible ETL Listed ROHS
	Warranty	5
	Mount	Surface
	Color Options	Brushed Nickel



MLLG-AL-LED-CAN12MV-20-CC-NK

20 Watt 12 In LED Flush Mounted Ceiling Light

Project Name



WebID: 1636

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
75	20	\$31.17	\$155.87

○ PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-WD-LED-BARN-45-50	45	6300	140
LLS-X-STL-4-50A-CC	30 40 50	4200 5300 6500	133
MLLG-AL-LED-LIN-SWL-44-CC-MS	22 28 36 44	3102 3948 5076 6204	141
MLLG-LN-LED-EXIT2-2L	2.4		NaN
LLS-HD-HM3-450-50-[V]-T5	450	69750	155
LLS-HD-HM3-600-50-[V]-T5	600	90000	150
MLLG-YA-LED-PT-100-CC	60 80 100	7800 10400 13000	130
LLS-LN-4FT-T8-18-5-C-25P	18	2160	120
LLS-LN-8FT-T8-36-5-F-25P	36	4320	120
LLS-LN-8FT-T8-44-65-C-25P	44	5700	130

