### MLLG-AL-LED-CAN14EMB-21-CC

21 Watt 14 Inch LED Flush Mounted Ceiling Light

Project Name



#### **DETAILS**

Flush-mounted LED ceiling lights are lighting fixtures designed to be installed directly on a ceiling surface. Our fixtures offer bright, efficient lighting for commercial, industrial, and even residential applications. Unlike recessed lighting, flush mounts do not require a cavity in the ceiling. They are perfect for low ceilings. Our flush-mounted LED lights come in a round shape and are offered in various sizes. They are available in different color temperatures, wattages, and lumen outputs. These fixtures are commonly used in offices, hallways, classrooms, storage rooms, and retail spaces.



Color Adjustable

OVE	OVERVIEW MILG-AL-LED-CAN14FMB-21-CC	
	WILLG-AL-LLD-CANT4LIVID-21-CG	
Watts	21	
Lumens	1470	
Lumens Per Watt (Efficacy)	70	
Color Temperature	3000K   4000K   5000K	
Voltage	100V-277V	



Product Dimensions	14 in D X 4.5 in H
Product Weight	3.75 lbs



Matta		Current An	np Draw	
Watts	120V	240V	277V	480V
21	0.18	0.09	0.08	0.04

















# MLLG-AL-LED-CAN14EMB-21-CC

21 Watt 14 Inch LED Flush Mounted Ceiling Light

Project Name



WebID: 1639

PRODUCT SPECIFICATIONS		
	Watts	21
	Lumens	1470
	Color Temperature	3000K   4000K   5000K
	CRI	80+
	Replaces	75W Incandescent
	Voltage	100-277
	Dimming	Triac
	Power Factor (PF)	50 / 60 hz
	Rated Life	50,000 hours
	Certifications	Rebate Eligible   ETL Listed   ROHS
	Warranty	5
	Mount	Surface
	Color Options	Brushed Nickel   Oil Rubbed Bronze



## MLLG-AL-LED-CAN14EMB-21-CC

21 Watt 14 Inch LED Flush Mounted Ceiling Light

Project Name



WebID: 1639

### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
75	21	\$30.61	\$153.04

### **PRODUCT FAMILY MODELS**

SKU	Watts	Lumens	Lumens/Watt
MLLG-WD-LED-BARN-45-50	45	6300	140
LLS-X-STL-4-50A-CC	30 40 50	4200 5300 6500	133
MLLG-AL-LED-LIN-SWL-44-CC-MS	22 28 36 44	3102 3948 5076 6204	141
MLLG-LN-LED-EXIT2-2L	2.4		NaN
LLS-HD-HM3-450-50-[V]-T5	450	69750	155
LLS-HD-HM3-600-50-[V]-T5	600	90000	150
MLLG-YA-LED-PT-100-CC	60 80 100	7800 10400 13000	130
LLS-LN-4FT-T8-18-5-C-25P	18	2160	120
LLS-LN-8FT-T8-36-5-F-25P	36	4320	120
LLS-LN-8FT-T8-44-65-C-25P	44	5700	130

