MLLG-AL-LED-CAN16MV-24-CC-NK

24 Watt 16 Inch LED Flush Mounted Ceiling Light

Project Name.



DETAILS

Flush-mounted LED ceiling lights are lighting fixtures designed to be installed directly on a ceiling surface. Our fixtures offer bright, efficient lighting for commercial, industrial, and even residential applications. Unlike recessed lighting, flush mounts do not require a cavity in the ceiling. They are perfect for low ceilings. Our flush-mounted LED lights come in a round shape and are offered in various sizes. They are available in different color temperatures, wattages, and lumen outputs. These fixtures are commonly used in offices, hallways, classrooms, storage rooms, and retail spaces.

SKU MLLG-AL-LED-CAN16MV-24-C Watts Lumens 17
Lumens 17
Lumens Per Watt (Efficacy)
Color Temperature 3000K 4000K 5000
Voltage 100V-27



₽ PRODUCT DIMENSIONS

2.5 lbs **Product Weight**















AMP DRAW

	Current Amp Draw				
Watts	120V	240V	277V	480V	
24	0.20	0.10	0.09	0.05	



MLLG-AL-LED-CAN16MV-24-CC-NK

24 Watt 16 Inch LED Flush Mounted Ceiling Light

Project Name _____



PRODUCT SPECIFICATIONS				
OPTICAL	Watts	24		
	Lumens	1700		
	Color Temperature	3000K 4000K 5000K		
	CRI	80+		
	Replaces	75W Incandescent		
ELECTRICAL	Voltage	100-277		
	Dimming	Triac		
	Power Factor (PF)	50 / 60 hz		
CONSTRUCTION	Rated Life	50,000 hours		
	Certifications	Energy Star Rebate Eligible ETL Listed ROHS		
	Warranty	5		
	Mount	Surface		
	Color Options	Brushed Nickel		



MLLG-AL-LED-CAN16MV-24-CC-NK

24 Watt 16 Inch LED Flush Mounted Ceiling Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
75	24	\$28.91	\$144.53

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-WD-LED-BARN-45-50	45	6300	140
LLS-X-STL-4-50A-CC	30 40 50	4200 5300 6500	133
MLLG-AL-LED-LIN-SWL-44-CC-MS	22 28 36 44	3102 3948 5076 6204	141
LLS-AL-DL-10-40A-CC	22 26 30 35 40	2640 3120 3600 4200 4800	120
MLLG-LN-LED-EXIT2-2L	2.4		NaN
MLLG-LN-LED-EXIT2-2L-B	5		0
LLS-HD-HM3-450-50-[V]-T5	450	69750	155
LLS-HD-HM3-600-50-[V]-T5	600	90000	150
LLS-HD-HM3-750-50-[V]-T5	750	112500	150
LLS-AL-BLP-2X2-30A-CC-EM-2P	20 25 30	2500 3125 3750	125
LLS-AL-PANBH-2X4-40A-CC-EM-2P	25 30 40	3250 3900 5200	130
MLLG-YA-LED-PT-100-CC	60 80 100	7800 10400 13000	130
LLS-LN-4FT-T8-18-5-C-25P	18	2160	120
LLS-LN-8FT-T8-36-5-F-25P	36	4320	120
LLS-LN-8FT-T8-44-65-C-25P	44	5700	130

