

# MLLG-E-LED-EXPLA2-100-50-C1D2

100 Watt Square Explosion Proof LED Light

Project Name \_\_\_\_\_



## DETAILS

Illuminate hazardous areas safely with our 100W explosion proof LED light delivering 13000 lumens of bright 5000K daylight. Class 1 Div 2 & Class 2 Div 2 certified for industrial facilities, chemical plants, oil refineries. Universal 100-277V input ensures reliable performance.

## OVERVIEW

|                            |                               |
|----------------------------|-------------------------------|
| SKU                        | MLLG-E-LED-EXPLA2-100-50-C1D2 |
| Watts                      | 100                           |
| Lumens                     | 13000                         |
| Lumens Per Watt (Efficacy) | 130                           |
| Color Temperature          | 5000K                         |
| Voltage                    | 100V-277V                     |



## PRODUCT DIMENSIONS

|                    |               |
|--------------------|---------------|
| Product Dimensions | 12 x 12 x 6.6 |
| Product Weight     | 17 lbs        |



## AMP DRAW

| Watts | Current Amp Draw |      |      |
|-------|------------------|------|------|
|       | 120V             | 240V | 277V |
| 100   | 0.83             | 0.42 | 0.36 |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

[www.ledlightingsupply.com](http://www.ledlightingsupply.com) (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID : 1804

# MLLG-E-LED-EXPLA2-100-50-C1D2

100 Watt Square Explosion Proof LED Light

Project Name \_\_\_\_\_



## PRODUCT SPECIFICATIONS

|                     |                              |                                    |
|---------------------|------------------------------|------------------------------------|
| <b>OPTICAL</b>      | <b>Watts</b>                 | 100                                |
|                     | <b>Lumens</b>                | 13000                              |
|                     | <b>Color Temperature</b>     | 5000K                              |
|                     | <b>CRI</b>                   | 70+                                |
|                     | <b>Beam Angles (Std)</b>     | 120°                               |
|                     | <b>Optics</b>                | Tempered Glass Lens                |
|                     | <b>Replaces</b>              | 250 Watt Metal Halide              |
| <b>ELECTRICAL</b>   | <b>Voltage</b>               | 100-277                            |
|                     | <b>Power Factor (PF)</b>     | >.98                               |
|                     | <b>THD</b>                   | < 10%                              |
|                     | <b>Dimming</b>               | No                                 |
|                     | <b>Surge Protection</b>      | 10kV                               |
|                     | <b>Power Factor (PF)</b>     | 50-60Hz                            |
| <b>CONSTRUCTION</b> | <b>Housing</b>               | Copper Free Aluminum               |
|                     | <b>IP Rating</b>             | IP68                               |
|                     | <b>IK Rating</b>             | IK09                               |
|                     | <b>Operating Temperature</b> | -22°F to 122°F                     |
|                     | <b>Rated Life</b>            | 50,000 (L70) hours                 |
|                     | <b>Certifications</b>        | Rebate Eligible   UL Listed   ROHS |
|                     | <b>Warranty</b>              | 5 years                            |
|                     | <b>Mount</b>                 | Pendant   Trunnion                 |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

 [www.ledlightingsupply.com](http://www.ledlightingsupply.com)  (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID : 1804

# MLLG-E-LED-EXPLA2-100-50-C1D2

100 Watt Square Explosion Proof LED Light

Project Name \_\_\_\_\_



## ⚡ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

| Metal Halide Watts | LED Watts | 1 Year Energy Savings | 5 Year Energy Savings |
|--------------------|-----------|-----------------------|-----------------------|
| 250                | 100       | \$85.02               | \$425.10              |

## ⌚ PRODUCT FAMILY MODELS

| SKU                           | Watts | Lumens | Lumens/Watt |
|-------------------------------|-------|--------|-------------|
| MLLG-E-LED-EXPLA2-100-50-C1D2 | 100   | 13000  | 130         |
| MLLG-E-LED-EXPLA2-200-50-C1D2 | 200   | 26000  | 130         |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

✉ [www.ledlightingsupply.com](http://www.ledlightingsupply.com) ☎ (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID : 1804