MLLG-YA-LED-WPFCD-100-50

100 Watt Full Cutoff LED Wall Pack

Project Name



DETAILS

100 watts full cutoff LED wall pack has a die-cast aluminum housing and an impact-resistant polycarbonate lens. It is the perfect replacement for metal halide outdoor wall packs. The housing makes quick and easy installation with a removable hinge door and multiple points of entry.

OVERVIEW		
SKU	MLLG-YA-LED-WPFCD-100-50	
Wattage	100	
Lumens	12900	
Lumens Per Watt (Efficacy)	129	
Color Temperature	5000K	
Voltage	100V-277V	



▶ PRODUCT DIMENSIONS

Product Dimensions 11.7 in L x 3.6 in W x 8.6 in D



AMP DRAW

Mattaga		Current Amp Draw		
wattage	Wattage 120V	240V	277V	480V
100	0.83	0.42	0.36	0.21



MLLG-YA-LED-WPFCD-100-50

100 Watt Full Cutoff LED Wall Pack

Project Name



WebID: 1816

PRODUCT SPECIFICATIONS		
	Wattage	100
	Lumens	12900
	Color Temperature	5000K
	CRI	70+
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	> .90
	THD	< 20%
	Power Factor (PF)	50-60Hz
	Housing	Powder Coated Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-40°F to +113°F
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible ETL Listed ROHS
	Warranty	5
	Mount	Wall
	Color Options	Bronze



MLLG-YA-LED-WPFCD-100-50

100 Watt Full Cutoff LED Wall Pack

Project Name



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
250	100	\$85.02	\$425.10

○ PRODUCT FAMILY MODELS

SKU	Wattage	Lumens	Lumens/Watt
MLLG-YA-LED-WPFCD-24-50	24	3100	129
MLLG-YA-LED-WPFCD-48-50	48	6400	133
MLLG-YA-LED-WPFCD-80-50	80	10300	129
MLLG-YA-LED-WPFCD-100-50	100	12900	129

