# MLLG-E-LED-EXPLC-250-50-[V]-C1D1

250 Watt Round Explosion Proof LED Light

Project Name



#### **DETAILS**

Our C Series C1D1 Explosion Proof fixtures come in both 120-277v and 277-480v configurations. At 140 lumens per watt they are an efficient and safe solution for environments where ignitable materials are present.

OVERV SKU MLI	/ <b>IEW</b> .G-E-LED-EXPLC-250-50-[V]-C1D1
Watts	250
Lumens	35000
Lumens Per Watt (Efficacy)	140
Color Temperature	5000K
Voltage	100V-277V   277V-480V

#### **▶** PRODUCT DIMENSIONS

Product Dimensions	16 in D x 13.5 in H
Product Weight	39 lbs

<b>☼ UL SPECS</b>
UL 844 Hazardous Locations
Class I, Division 1, Groups C,D
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III
UL 1598 Suitable for Wet Locations
UL 1598A Marine Outside Type
ABS













WebID: 1858



# MLLG-E-LED-EXPLC-250-50-[V]-C1D1

250 Watt Round Explosion Proof LED Light

Project Name



WebID: 1858

PRODUCT SPECIFICATIONS		
	Watts	250
	Lumens	35000
	Color Temperature	5000K
	CRI	70+
	Replaces	400 Watt Metal Halide
	Voltage	100-277   277-480
	Power Factor (PF)	>.95
	THD	< 10%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	IP Rating	IP66
	IK Rating	IK10
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible   ETL Listed   ROHS   CB
	Warranty	5
	Mount	Yoke   3/4 in NPT Pendant
	Color Options	Gray



# MLLG-E-LED-EXPLC-250-50-[V]-C1D1

250 Watt Round Explosion Proof LED Light

Project Name



WebID: 1858

#### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	250	\$85.02	\$425.10

### **PRODUCT FAMILY MODELS**

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLC-40-50-C1D1	40	5600	140
MLLG-E-LED-EXPLC-60-50-[V]-C1D1	60	8400	140
MLLG-E-LED-EXPLC-80-50-[V]-C1D1	80	11200	140
MLLG-E-LED-EXPLC-100-50-[V]-C1D1	100	14000	140
MLLG-E-LED-EXPLC-150-50-[V]-C1D1	150	21000	140
MLLG-E-LED-EXPLC-200-50-[V]-C1D1	200	28000	140
MLLG-E-LED-EXPLC-250-50-[V]-C1D1	250	35000	140
MLLG-E-LED-EXPLC-250-50-[V]-C1D1	250	35000	140

