

# MLLG-WD-LED-WRAP-4-40-CC

30 / 35 / 40 Watt Adjustable LED Wraparound Light

Project Name \_\_\_\_\_



## DETAILS

4 foot 30 | 35 | 40 Power Adjustable and 3500K or 4000K or 5000K Color Adjustable LED wrap-around shop light. The LEDs and driver are enclosed creating a seamless appearance and preventing dust or debris from entering the unit. This fixture mounts directly to the ceiling. All hardware is included with this fixture.

✔ Color Adjustable    ✔ Wattage Adjustable

## OVERVIEW

|                            |                          |
|----------------------------|--------------------------|
| SKU                        | MLLG-WD-LED-WRAP-4-40-CC |
| Watts                      | 30   35   40             |
| Lumens                     | 4110   4690   5240       |
| Lumens Per Watt (Efficacy) | 131                      |
| Color Temperature          | 3500K   4000K   5000K    |
| Voltage                    | 100V-277V                |



## ↗ PRODUCT DIMENSIONS

Product Weight 7.94 lbs

## ☀ AMP DRAW

| Watts | Current Amp Draw |      |      |      |
|-------|------------------|------|------|------|
|       | 120V             | 240V | 277V | 480V |
| 30    | 0.25             | 0.13 | 0.11 | 0.06 |
| 35    | 0.29             | 0.15 | 0.13 | 0.07 |
| 40    | 0.33             | 0.17 | 0.14 | 0.08 |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

🌐 [www.ledlightingsupply.com](http://www.ledlightingsupply.com) ☎ (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID : 1924

# MLLG-WD-LED-WRAP-4-40-CC

30 / 35 / 40 Watt Adjustable LED Wraparound Light

Project Name \_\_\_\_\_



## PRODUCT SPECIFICATIONS

|              |                       |                                               |
|--------------|-----------------------|-----------------------------------------------|
| OPTICAL      | Watts                 | 30   35   40                                  |
|              | Lumens                | 4110   4690   5240                            |
|              | Color Temperature     | 3500K   4000K   5000K                         |
|              | CRI                   | 80+                                           |
|              | Replaces              | 100 Watt Metal Halide   150 Watt Metal Halide |
| ELECTRICAL   | Voltage               | 100-277                                       |
|              | Power Factor (PF)     | > .90                                         |
|              | Dimming               | 1-10V                                         |
|              | Power Factor (PF)     | 50-60Hz                                       |
| CONSTRUCTION | IP Rating             | IP20                                          |
|              | Operating Temperature | -4°F to +122°F                                |
|              | Rated Life            | 70,000 hours                                  |
|              | Certifications        | Rebate Eligible   UL Listed   ROHS            |
|              | Warranty              | 5                                             |
|              | Mount                 | Surface                                       |
|              | Color Options         | White                                         |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

 [www.ledlightingsupply.com](http://www.ledlightingsupply.com)  (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID : 1924

# MLLG-WD-LED-WRAP-4-40-CC

30 / 35 / 40 Watt Adjustable LED Wraparound Light

Project Name \_\_\_\_\_



## ⚡ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

| Metal Halide Watts | LED Watts | 1 Year Energy Savings | 5 Year Energy Savings |
|--------------------|-----------|-----------------------|-----------------------|
| 150                | 30        | \$68.02               | \$340.08              |
| 150                | 35        | \$65.18               | \$325.91              |
| 150                | 40        | \$62.35               | \$311.74              |

## 🔍 PRODUCT FAMILY MODELS

| SKU                           | Watts          | Lumens                   | Lumens/Watt |
|-------------------------------|----------------|--------------------------|-------------|
| MLLG-WD-LED-BARN-45-50        | 45             | 6300                     | 140         |
| LLS-X-STL-4-50A-CC            | 30 40 50       | 4200 5300 6500           | 133         |
| MLLG-AL-LED-LIN-SWL-44-CC-MS  | 22 28 36 44    | 3102 3948 5076 6204      | 141         |
| LLS-AL-DL-10-40A-CC           | 22 26 30 35 40 | 2640 3120 3600 4200 4800 | 120         |
| MLLG-LN-LED-EXIT2-2L          | 2.4            |                          | NaN         |
| MLLG-LN-LED-EXIT2-2L-B        | 5              |                          | 0           |
| LLS-HD-HM3-450-50-[V]-T5      | 450            | 69750                    | 155         |
| LLS-HD-HM3-600-50-[V]-T5      | 600            | 90000                    | 150         |
| LLS-HD-HM3-750-50-[V]-T5      | 750            | 112500                   | 150         |
| LLS-AL-BLP-2X2-30A-CC-EM-2P   | 20 25 30       | 2500 3125 3750           | 125         |
| LLS-AL-PANBH-2X4-40A-CC-EM-2P | 25 30 40       | 3250 3900 5200           | 130         |
| MLLG-YA-LED-PT-100-CC         | 60 80 100      | 7800 10400 13000         | 130         |
| LLS-LN-4FT-T8-18-5-C-25P      | 18             | 2160                     | 120         |
| LLS-LN-8FT-T8-36-5-F-25P      | 36             | 4320                     | 120         |
| LLS-LN-8FT-T8-44-65-C-25P     | 44             | 5700                     | 130         |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

🌐 [www.ledlightingsupply.com](http://www.ledlightingsupply.com) ☎️ (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID : 1924