MLLG-E-LED-EXPLI2-50-50-U-C1D1

50 Watt Explosion Proof Linear LED Light

Project Name _



DETAILS

50 Watt LED Explosion Proof - Class 1 Division 1 light is a compact linear fixture that replaces fluorescent lighting for hazardous locations. This is a die-cast aluminum fixture designed for industrial hazardous locations.

OVERVIEW			
sku	MLLG-E-LED-EXPLI2-50-50-U- C1D1		
Watts	50		
Lumens	7000		
Lumens Per Watt (Efficacy)	140		
Color Temperature	5000K		
Voltage	100V-277V 277V-480V Optional		



₽ PRODUCT DIMENSIONS

Product Weight	20 lbs
i ioddol weigiit	20 103





UL SPECS

UL 844 Hazardous Locations
Class I, Division 1, Groups C,D
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III
UL 1598 Suitable for Wet Locations
UL 1598A Marine Outside Type
ABS



MLLG-E-LED-EXPLI2-50-50-U-C1D1

50 Watt Explosion Proof Linear LED Light

Project Name _____



PRODUCT SPECIFICATIONS				
OPTICAL	Watts	50		
	Lumens	7000		
	Color Temperature	5000K		
	CRI	70+		
	Replaces	250 Watt Metal Halide		
ELECTRICAL	Voltage 100-277 277-480 Optional			
	Power Factor (PF)	>.95		
	THD	< 10%		
	Dimming	1-10V		
	Power Factor (PF)	50-60Hz		
CONSTRUCTION	IP Rating	IP66		
IK Rating		IK10		
	Rated Life	50,000 (L70) hours		
	Certifications	Rebate Eligible ETL Listed NSF Certified ROHS CB		
	Warranty	5		
	Mount	Yoke 3/4 in NPT Pendant		
	Color Options	Gray		



MLLG-E-LED-EXPLI2-50-50-U-C1D1

50 Watt Explosion Proof Linear LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	50	\$113.36	\$566.80

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLI2-50-50-U-C1D1	50	7000	140
MLLG-E-LED-EXPLI-40-50-[V]-C1D1	40	5600	140
MLLG-E-LED-EXPLI-60-50-[V]-C1D1	60	8400	140
MLLG-E-LED-EXPLI-80-50-[V]-C1D1	80	11200	140
MLLG-E-LED-EXPLI-100-50-[V]-C1D1	100	14000	140

