MLLG-E-LED-EXPLP14-60-50-C1D2

60 Watt Explosion Proof 1x4 Low Profile Linear LED Light

Project Name



DETAILS

60 Watt LED Explosion Proof 1X4 panel - Class 1 Division 2 light replaces fluorescent lighting for hazardous locations. The fixture can work as a surface mount, ceiling mount, and recessed mount. Integrated emergency backup module is optional.



Explosion Proof C1D2

OVERVIEW KU MLLG-E-LED-EXPLP14-60-50-C1D2		
Watts	60	
Lumens	8400	
Lumens Per Watt (Efficacy)	140	
Color Temperature	5000K	
Voltage	100V-277V	



▶ PRODUCT DIMENSIONS

Product Dimensions	49.2 in L X 12 in W X 3.7 in H
Product Weight	44 lbs











WebID: 1939

UL SPECS UL 844 Hazardous Locations Class 1, Division 2, Groups A,B,C,D Class 2, Division 1, Groups F,G Class 3



MLLG-E-LED-EXPLP14-60-50-C1D2

60 Watt Explosion Proof 1x4 Low Profile Linear LED Light

Project Name



WebID: 1939

PRODUCT SPECIFICATIONS		
	Watts	60
	Lumens	8400
	Color Temperature	5000K
	CRI	70+
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	>.95
	THD	< 10%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	IP Rating	IP66
	IK Rating IK09	
	Operating Temperature	-40°F to 140°F
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible UL Listed NSF Certified ROHS CB
	Warranty	5
	Mount	Chain-Cable Recessed Surface



MLLG-E-LED-EXPLP14-60-50-C1D2

60 Watt Explosion Proof 1x4 Low Profile Linear LED Light

Project Name _____



WebID: 1939

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	60	\$107.69	\$538.46

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLP12-40-50-C1D2	40	5600	140
MLLG-E-LED-EXPLP14-40-50-C1D2	40	5600	140
MLLG-E-LED-EXPLP14-60-50-C1D2	60	8400	140
MLLG-E-LED-EXPLP22-40-50-C1D2	40	5600	140
MLLG-E-LED-EXPLP22-60-50-C1D2	60	840	14
MLLG-E-LED-EXPLP22-80-50-C1D2	80	11200	140
MLLG-E-LED-EXPLP24-60-50-C1D2	60	8400	140
MLLG-E-LED-EXPLP24-80-50-C1D2	80	11200	140
MLLG-E-LED-EXPLP24-100-50-C1D2	100	14000	140
MLLG-E-LED-EXPLP24-120-50-C1D2	120	16800	140

