MLLG-E-LED-EXPLB-250-[V]-C1D2

250 Watt Explosion Proof Round LED Light

Project Name



DETAILS

250 Watt LED Explosion Proof - is a powerful, energy efficient class 1 division 2 light designed to work in hazardous conditions and areas. These lights are powerful enough to replace the lumen output of 1000 watts metal halide. These lights are extremely robust and designed to be reliable for years of maintenance free operation.

OVEF SKU	RVIEW MLLG-E-LED-EXPLB-250-[V]-C1D2
Watts	250 300 400
Lumens	35000 42000 56000
Lumens Per Watt (Efficacy)	140
Color Temperature	5000K
Voltage	100V-277V 277V-480V



▶ PRODUCT DIMENSIONS

Product Dimensions	18.9 X 15.5 in
Product Weight	37.5 lbs



UL 844 Hazardous Locations
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III
UL 1598 Suitable for Wet Locations
UL 1598A Marine Outside Type
ABS



MLLG-E-LED-EXPLB-250-[V]-C1D2

250 Watt Explosion Proof Round LED Light

Project Name



WebID: 1961

PRODUCT SPECIFICATIONS			
	Watts	250 300 400	
	Lumens	35000 42000 56000	
	Color Temperature	5000K	
	CRI	70+	
	Replaces	1000 Watt Metal Halide	
	Voltage	100-277 277-480	
	Power Factor (PF)	>.95	
	THD	<10%	
	Dimming	1-10V	
	Power Factor (PF)	50-60Hz	
	IP Rating	IP66	
	Rated Life	50,000 (L70) hours	
	Certifications	Rebate Eligible ETL Listed ROHS CB	
	Warranty	5	
	Mount	Yoke 3/4 in NPT Pendant	
	Color Options	Gray	



MLLG-E-LED-EXPLB-250-[V]-C1D2

250 Watt Explosion Proof Round LED Light

Project Name _____



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
1000	250	\$425.10	\$2,125.50
1000	300	\$396.76	\$1,983.80
1000	400	\$340.08	\$1,700.40

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLB-40-50-[V]-C1D2	40	5600	140
MLLG-E-LED-EXPLB-60-50-[V]-C1D2	60	8400	140
MLLG-E-LED-EXPLB-80-50-[V]-C1D2	80	11200	140
MLLG-E-LED-EXPLB-100-50-[V]-C1D2	100	14000	140
MLLG-E-LED-EXPLB-150-50-[V]-C1D2	150	21000	140
MLLG-E-LED-EXPLB-200-50-[V]-C1D2	200	28000	140
MLLG-E-LED-EXPLB-250-[V]-C1D2	250 300 400	35000 42000 56000	140
MLLG-E-LED-EXPLB-300-50-[V]-C1D2	300	42000	140
MLLG-E-LED-EXPLB-400-50-[V]-C1D2	400	56000	140

