MLLG-E-LED-EXPLC-40-50-C1D1

40 Watt Round Explosion Proof LED Light



DETAILS

Our Round C Series C1D1 Explosion Proof fixtures produce 140 lumens per watt making them a highly efficient and safe solution for environments where ignitable materials are present.

 _				
 1 -	• 1	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		ı
 13	7.4		F W	١.
 	1.		LI	П

SKU	MLLG-E-LED-EXPLC-40-50-C1D1
Watts	40
Lumens	5600
Lumens Per Watt (Efficacy)	140
Color Temperature	5000K
Voltage	100V-277V 277V-480V



30.9 lbs **Product Weight**

UL SPECS

UL	844	Hazardous	Locations

Class I, Division 1, Groups C,D

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations

UL 1598A Marine Outside Type

ABS















MLLG-E-LED-EXPLC-40-50-C1D1

40 Watt Round Explosion Proof LED Light

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	40	
	Lumens	5600	
	Color Temperature	5000K	
	CRI	70+	
	Replaces	150 Watt Metal Halide	
ELECTRICAL	Voltage	100-277 277-480	
	Power Factor (PF)	>.95	
	THD	< 10%	
	Dimming	1-10V	
	Power Factor (PF)	50-60Hz	
CONSTRUCTION	IP Rating	IP66	
	IK Rating	IK10	
Rated Life		50,000 (L70) hours	
	Certifications	Rebate Eligible ETL Listed ROHS CB	
	Warranty	5	
	Mount Yoke 3/4 in NPT Pendant		
	Color Options	Gray	



MLLG-E-LED-EXPLC-40-50-C1D1

40 Watt Round Explosion Proof LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
150	40	\$62.35	\$311.74

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLC-40-50-C1D1	40	5600	140
MLLG-E-LED-EXPLC-60-50-[V]-C1D1	60	8400	140
MLLG-E-LED-EXPLC-80-50-[V]-C1D1	80	11200	140
MLLG-E-LED-EXPLC-100-50-[V]-C1D1	100	14000	140
MLLG-E-LED-EXPLC-150-50-[V]-C1D1	150	21000	140
MLLG-E-LED-EXPLC-200-50-[V]-C1D1	200	28000	140
MLLG-E-LED-EXPLC-250-50-[V]-C1D1	250	35000	140

