MLLG-LED-EXPLF2-40-50-C1D2-V2

40 Watt 2 Foot Low Profile Explosion Proof LED Linear Light

Project Name _



DETAILS

40 Watt LED Explosion Proof - Class 1 Division 2 light is a compact linear fixture that replaces fluorescent lighting for hazardous locations. This is a die cast aluminum fixture with clear polycarbonate lens diffuser. It is dust proof.

OVERVIEW			
sku	MLLG-LED-EXPLF2-40-50-C1D2- V2		
Watts	40		
Lumens	5600		
Lumens Per Watt (Efficacy)	140		
Color Temperature	5000K		
Voltage	100V-277V		



Product Weight 17 lbs











CSA / ATEX / IECEX

Class 1 Division 2, Group B,C,D Class 2, Division 2, Groups F,G Class 3 Wet Locations (UL 1598 / UL1598A) **UL844**



MLLG-LED-EXPLF2-40-50-C1D2-V2

40 Watt 2 Foot Low Profile Explosion Proof LED Linear Light

Project Name _____



PRODUCT SPECIFICATIONS					
OPTICAL	Watts	40			
	Lumens	5600			
	Color Temperature	5000K			
	CRI	70+			
	Replaces	175 Watt Metal Halide			
ELECTRICAL	Voltage	100-277			
	Power Factor (PF)	>.95			
	THD	< 10%			
Dimmi		1-10V			
	Power Factor (PF)	50-60Hz			
CONSTRUCTION	IP Rating	IP66			
	Operating Temperature	-40°F to 131°F			
	Rated Life	50,000 (L70) hours			
	Certifications	Rebate Eligible UL Listed NSF Certified ROHS CB			
	Warranty	5			
	Mount	Bracket Surface Wall			
	Color Options	Gray			



MLLG-LED-EXPLF2-40-50-C1D2-V2

40 Watt 2 Foot Low Profile Explosion Proof LED Linear Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
175	40	\$76.52	\$382.59

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-LED-EXPLF2-40-50-C1D2-V2	40	5600	140
MLLG-LED-EXPLF4-60-50-C1D2	60	8400	140
MLLG-LED-EXPLF4-80-50-C1D2-V2	80	11200	140

