MLLG-LED-SBHO2-150-50B

150 Watt LED Billboard Light

Project	Nama	
rioject	INAIIIE	



DETAILS

LED Lighting Supply billboard lights are a specific type of floodlight. They use specialized optics to project bright, high-quality light evenly across small and large billboards. Our billboard lights are mounted at the top or bottom of the outdoor sign. They are set back usually 4 to 8 feet from the face of the sign. You can easily replace metal halide billboard lights with LED for outdoor advertising.



Photocell

OVERVIEW SKU MLLG-LED-SBH02-150-50B		
Watts	150	
Lumens	24000	
Lumens Per Watt (Efficacy)	160	
Color Temperature	4000K 5000K	
Voltage	100V-277V 277V-480V	



▶ PRODUCT DIMENSIONS

Product Dimensions	15.63 in L X 11.25 in W X 3.22 in H
Product Weight	9.48 lbs



AMP DRAW

Watts	Current Amp Draw			
Walls	120V	240V	277V	480V
150	1.25	0.63	0.54	0.31



MLLG-LED-SBHO2-150-50B

150 Watt LED Billboard Light

Project Name



WebID: 2021

PRODUCT SPECIFICATIONS		
	Watts	150
	Lumens	24000
	Color Temperature	4000K 5000K
	CRI	70+
	Beam Angles	Type 3, 5
	Replaces	400 Watt Metal Halide
	Voltage	100-277 277-480
	Power Factor (PF)	> .92
	THD	< 15%
	Dimming	1-10V
	Surge Protection	6kV line-line, 10kV line-earth
	Power Factor (PF)	50-60Hz
	Housing	Die-Cast Aluminum
	IP Rating	IP65
	IK Rating	IK08
	Operating Temperature	-22°F to +113°F
	Rated Life	244,000 (L70) hours
	Certifications	DLC Premium ETL Listed ROHS
	Warranty	10 years
	Mount	Yoke Slip Fitter
	Color Options	Bronze



MLLG-LED-SBHO2-150-50B

150 Watt LED Billboard Light

Project Name



WebID: 2021

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	150	\$141.70	\$708.50

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-LED-SBHO2-150-50B	150	24000	160
MLLG-LED-SBHO2-300-50B	300	48000	160
MLLG-LED-SBHO2-150-50	150	24000	160
MLLG-LED-SBHO2-300-50	300	48000	160

