# MLLG-LS-LED-FLD2-35-CC-[Mount]

15 / 25 / 35 Watt Adjustable LED Flood Light

Project Name



#### **DETAILS**

Yoke or 1/2 inch knuckle mount low wattage flood lights are ideal for lighting up spaces from a 10 to 15 foot mounting height. Wattage and color adjustable to fine tune the light to your application.



Wattage Adjustable

OVERVIEW			
sкu	MLLG-LS-LED-FLD2-35-CC-[Mount]		
Wattage	15   25   35		
Lumens	2025   2700   4700		
Lumens Per Watt (Efficacy)	135		
Color Temperature	3000K   4000K   5000K		
Voltage	100V-277V		



Product Dimensions	9.8 in L X 6.9 in W
Product Weight	5 lbs



SKU	Mounting
MLLG-LS-LED-FLD2-35-CC-KM	Knuckle
MLLG-LS-LED-FLD2-35-CC-YM	Yoke















WebID: 2028



# MLLG-LS-LED-FLD2-35-CC-[Mount]

15 / 25 / 35 Watt Adjustable LED Flood Light

Project Name



WebID: 2028

PRODUCT SPECIFICATIONS		
	Wattage	15   25   35
	Lumens	2025   2700   4700
	Color Temperature	3000K   4000K   5000K
	CRI	70+
	Replaces	100 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	.9
	THD	15%
	Dimming	No
	Power Factor (PF)	50-60Hz
	Housing	Powder Coated Aluminum
	IP Rating	IP65
	Operating Temperature	-4°F to +140°F
	Rated Life 50,000 (L70) hours	
	Certifications	Rebate Eligible   UL Listed   ROHS
	Warranty	5
	Mount	Yoke   Knuckle
	Color Options	Bronze



# MLLG-LS-LED-FLD2-35-CC-[Mount]

15 / 25 / 35 Watt Adjustable LED Flood Light

Project Name



WebID: 2028

#### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
100	15	\$48.18	\$240.89
100	25	\$42.51	\$212.55
100	35	\$36.84	\$184.21

#### **PRODUCT FAMILY MODELS**

	SKU	Wattage	Lumens	Lumens/Watt
	MLLG-WD-LED-BARN-45-50	45	6300	140
MLLG-AG-LED-IMF-600-5-[Optic]-TR-[V		600	84000	140

### AMP DRAW

Wattaga		Current Amp Draw		
Wattage	120V	240V	277V	480V
15	0.13	0.06	0.05	0.03
25	0.21	0.10	0.09	0.05
35	0.29	0.15	0.13	0.07

