MLLG-X-LED-FD3-150-50-120

150 Watt LED Food Grade Light

Project Name _



DETAILS

150 Watt NSF LED fixture has an easy-to-clean, corrosion-resistant aluminum fixture housing and stainless steel eye hook to make the installation process easier. A 6.5 foot cord is included. This light offers protection against water pressure of 100 bar (1450 psi) and temperatures of 45C.Certified by the National Sanitation Foundation (NSF) as safe for food service processing facilities that require a higher level of sanitation. By NSF certification, these fixtures are certified shatterproof.

OVERVIEW			
SKU	MLLG-X-LED-FD3-150-50-120		
Watts	150		
Lumens	22500		
Lumens Per Watt (Efficacy)	150		
Color Temperature	5000K		
Voltage	100V-277V		



₽ PRODUCT DIMENSIONS

Product Weight 18 lbs



	Current Amp Draw			
Watts	120V	240V	277V	480V
150	1.25	0.63	0.54	0.31











MLLG-X-LED-FD3-150-50-120

150 Watt LED Food Grade Light

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	150	
	Lumens	22500	
	Color Temperature	5000K	
	CRI	80+	
	Replaces	400 Watt Metal Halide	
ELECTRICAL	Voltage	100-277	
	Power Factor (PF)	.93	
	THD	20% Max	
	Dimming	1-10V	
	Power Factor (PF)	50 / 60 hz	
CONSTRUCTION	IP Rating	IP66	
	IK Rating	IK08	
	Rated Life	60,000 (L70) hours	
	Certifications	DLC Premium UL Listed NSF Certified ROHS	
	Warranty	5	
	Mount	Eye-Hook (std) Pendant (std)	
	Color Options	White	



MLLG-X-LED-FD3-150-50-120

150 Watt LED Food Grade Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	150	\$141.70	\$708.50

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-X-LED-FD3-150-50-120	150	22500	150
MLLG-X-LED-FD3-200-50-120	200	30400	152

