MLLG-E-MS-C1D2-JB

Explosion Proof Junction Box

Project Name _____



DETAILS

C1D2 Explosion Proof Junction Box with built-in Motion Sensor functionality (on/off only). 3/8 inch knockout standard, 1/2 inch knockout special order.

Motion Sensor

MLLG-E-MS-C1D2-JB



▶ PRODUCT DIMENSIONS

UL SPECS

UL 844 Hazardous Locations

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations

UL 1598A Marine Outside Type

ABS





MLLG-E-MS-C1D2-JB

Explosion Proof Junction Box

Project Name _____



PRODUCT SPECIFICATIONS					
OPTICAL ELECTRICAL	_				
CONSTRUCTION	IP Rating	IP65			
	Operating Temperature	-76°F to 140°F			
	Certifications	ETL Listed ROHS			
	Warranty	5			



MLLG-E-MS-C1D2-JB

Explosion Proof Junction Box

Project Name _____



PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-MS-C1D1-JB			NaN
MLLG-E-MS-C1D2-JB			NaN

