MLLG-E-LED-EXPLG-20-50-C1D1

20 Watt Explosion Proof Jelly Jar LED Light

Project Name _____



DETAILS

Our Class 1 Division 1 (C1D1) Jelly Jar lights are ideal for a industrial locations with explosion proof requirements they come with a glass dome and metal cage. Pendant and surface mount standard.

OVERVIEW				
MLLG-E-LED-EXPLG-20-50-C1D1				
20				
2800				
140				
5000K				
100V-277V				

E I KODOOI DIMEKSIONS

Product Weight 14 lbs



UL 844 Hazardous Locations					
Class I, Division 1, Groups C,D					

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations

UL 1598A Marine Outside Type

ABS















MLLG-E-LED-EXPLG-20-50-C1D1

20 Watt Explosion Proof Jelly Jar LED Light

Project Name _____



PRODUCT SPECIFICATIONS					
OPTICAL	Watts	20			
	Lumens	2800			
	Color Temperature	5000K			
	CRI	70+			
	Replaces	100 Watt Metal Halide			
ELECTRICAL	Voltage	100-277			
	Power Factor (PF)	>.95			
	THD	< 10%			
	Dimming	No			
	Power Factor (PF)	50-60Hz			
CONSTRUCTION	IP Rating	IP66			
	IK Rating	IK10			
	Rated Life	50,000 (L70) hours			
	Certifications	Rebate Eligible ETL Listed ROHS			
	Warranty	5			
	Mount	Surface (std) 3/4 in NPT Pendant			



MLLG-E-LED-EXPLG-20-50-C1D1

20 Watt Explosion Proof Jelly Jar LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
100	20	\$45.34	\$226.72

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLG-20-50-C1D1	20	2800	140
MLLG-E-LED-EXPLG-30-50-C1D1	30	3900	130
MLLG-E-LED-EXPLG-40-50-C1D1	40	5200	130

5 SAMPLE COMPLETED PROJECTS WITH THIS PRODUCT



