

# MLLG-WL-LED-HBLIN6-270-CC

200 / 230 / 270 Wattage Adjustable High Bay Linear LED

Project Name \_\_\_\_\_



## DETAILS

200 / 230 / 270 Wattage Adjustable 2.5 Foot LED Linear Bay Light provides exceptional lighting solutions, combining efficiency and durability for various industrial and commercial applications.



Color Adjustable



Wattage Adjustable

## OVERVIEW

SKU MLLG-WL-LED-HBLIN6-270-CC

Watts 200 | 230 | 270

Lumens 31200 | 34700 | 39700

Lumens Per Watt (Efficacy) 150

Color Temperature 4000K | 5000K

Voltage 100V-277V



## PRODUCT DIMENSIONS

Product Dimensions 31.2 X 10.2 X 1.8 in

Product Weight 10 lbs



## AMP DRAW

| Watts | Current Amp Draw |      |      |      |
|-------|------------------|------|------|------|
|       | 120V             | 240V | 277V | 480V |
| 200   | 1.67             | 0.83 | 0.72 | 0.42 |
| 230   | 1.92             | 0.96 | 0.83 | 0.48 |
| 270   | 2.25             | 1.13 | 0.97 | 0.56 |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

[www.ledlightingsupply.com](http://www.ledlightingsupply.com) (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2122

# MLLG-WL-LED-HBLIN6-270-CC

200 / 230 / 270 Wattage Adjustable High Bay Linear LED

Project Name \_\_\_\_\_



## PRODUCT SPECIFICATIONS

|  |                              |                                                 |
|--|------------------------------|-------------------------------------------------|
|  | <b>Watts</b>                 | 200   230   270                                 |
|  | <b>Lumens</b>                | 31200   34700   39700                           |
|  | <b>Color Temperature</b>     | 4000K   5000K                                   |
|  | <b>CRI</b>                   | 80+                                             |
|  | <b>Replaces</b>              | 1000 Watt Metal Halide   1500 Watt Metal Halide |
|  | <b>Voltage</b>               | 100-277                                         |
|  | <b>Power Factor (PF)</b>     | .98                                             |
|  | <b>THD</b>                   | 20% Max                                         |
|  | <b>Dimming</b>               | 0-10V                                           |
|  | <b>Power Factor (PF)</b>     | 50 / 60 hz                                      |
|  | <b>Housing</b>               | Galvanized Rolled Iron                          |
|  | <b>Operating Temperature</b> | -4°F to 122°F                                   |
|  | <b>Rated Life</b>            | 70,000 hours                                    |
|  | <b>Certifications</b>        | Rebate Eligible   UL Listed   ROHS              |
|  | <b>Warranty</b>              | 5                                               |
|  | <b>Mount</b>                 | Chain-Cable (std)   Pendant   Surface           |
|  | <b>Color Options</b>         | White                                           |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

 [www.ledlightingsupply.com](http://www.ledlightingsupply.com)  (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2122

# MLLG-WL-LED-HBLIN6-270-CC

200 / 230 / 270 Wattage Adjustable High Bay Linear LED

Project Name \_\_\_\_\_



## ⚡ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

| Metal Halide Watts | LED Watts | 1 Year Energy Savings | 5 Year Energy Savings |
|--------------------|-----------|-----------------------|-----------------------|
| 1500               | 200       | \$736.84              | \$3,684.20            |
| 1500               | 230       | \$719.84              | \$3,599.18            |
| 1500               | 270       | \$697.16              | \$3,485.82            |

## 🔍 PRODUCT FAMILY MODELS

| SKU                            | Watts       | Lumens            | Lumens/Watt |
|--------------------------------|-------------|-------------------|-------------|
| MLLG-WL-LED-HBLIN6-170-CC-HV   | 170         | 23120             | 136         |
| MLLG-WL-LED-HBLIN6-270-CC      | 200 230 270 | 31200 34700 39700 | 150         |
| MLLG-WL-LED-HBLIN6-4-300-CC-HV | 300         | 40800             | 136         |
| MLLG-WL-LED-HBLIN6-4-400-CC    | 270 340 400 | 41600 50000 56100 | 150         |



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

🌐 [www.ledlightingsupply.com](http://www.ledlightingsupply.com) ☎ (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2122