LLS-X-HB8-150/120/100-CC

100 / 120 / 150 Watt Adjustable LED UFO High Bay

Project Name



DETAILS

Our commercial and industrial project partners rely on this adjustable UFO high bay fixture to enhance visibility and amplify worker safety. Engineered with advanced CRI, this fixture reduces the risk of worker injury in warehouses and factories. It can be equipped with motion sensor technology in high foot traffic zones, providing enhanced energy efficiency benefits while minimizing facility maintenance costs. If mitigating safety hazards and maximizing productivity are top-of-mind, this fixture is the ideal solution.

OVERVIEW			
SKU	LLS-X-HB8-150/120/100-CC		
Watts	100 120 150		
Lumens	15000 18000 22500		
Lumens Per Watt (Efficacy)	150		
Color Temperature	4000K 5000K		
Voltage	100V-277V		



₽ PRODUCT DIMENSIONS

Product Weight 4.5 lbs



14/-44-				
Watts	120V	240V	277V	480V
100	0.83	0.42	0.36	0.21
120	1.00	0.50	0.43	0.25
150	1.25	0.63	0.54	0.31


















LLS-X-HB8-150/120/100-CC

100 / 120 / 150 Watt Adjustable LED UFO High Bay

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	100 120 150	
	Lumens	15000 18000 22500	
	Color Temperature	4000K 5000K	
	CRI	80+	
	Replaces	250 Watt Metal Halide 400 Watt Metal Halide	
ELECTRICAL	Voltage	100-277	
	Power Factor (PF)	.90	
	THD	20% Max	
	Dimming	0-10V	
	Power Factor (PF)	50 / 60 hz	
CONSTRUCTION	IP Rating	IP65	
	IK Rating	IK10	
	Rated Life	50,000 (L70) hours	
	Certifications	DLC Premium UL Listed ROHS	
	Warranty	5	
	Mount	Eye-Hook (std) Surface	
	Color Options	Black	



LLS-X-HB8-150/120/100-CC

100 / 120 / 150 Watt Adjustable LED UFO High Bay

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	100	\$170.04	\$850.20
400	120	\$158.70	\$793.52
400	150	\$141.70	\$708.50

○ PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-X-HB8-150/120/100-CC	100 120 150	15000 18000 22500	150
LLS-X-HB8-240/200/180-CC	180 200 240	27000 30000 36000	150
LLS-X-HB8-310/270/240-CC	240 270 310	34800 39150 45000	145
LLS-X-HB8-150-5-HV	150	21700	145
LLS-X-HB8-240-5-HV	240	36000	150
LLS-X-HB8-310-5-HV	310	45000	145

