

# MLLG-POLE-WD-20-C5-T-SYP

20 Foot Wood Pole

Project Name \_\_\_\_\_



### DETAILS

Southern Yellow Pine is species found south of the Mason-Dixon line and east of the Great Plains in the USA. It is known for its strength, stiffness, and density making it an ideal material for utility poles. It is effective in holding nails and other types of fasteners. The cellular structure makes it suitable for the pressure treatment process. Nearly 85% of all pressure-treated wood in the U.S. is southern yellow pine.

CCA Treated to Prevent Insect and Rot Damage

Up to 50+ Years Service Life

1-year warranty

Manufactured in the USA

OVERVIEW	
SKU:	MLLG-POLE-WD-20-C5-T-SYP
Warranty	1-year warranty
Species	
Treatment	CCA
ANSI Class	Class 5



## PRODUCT FAMILY MODELS

SKU	Total Height	ANSI Class
MLLG-POLE-WD-20-C1-T-SYP	20 Feet	Class 1
MLLG-POLE-WD-20-C2-T-SYP	20 Feet	Class 2
MLLG-POLE-WD-20-C3-T-SYP	20 Feet	Class 3
MLLG-POLE-WD-20-C4-T-SYP	20 Feet	Class 4
MLLG-POLE-WD-20-C5-T-SYP	20 Feet	Class 5
MLLG-POLE-WD-20-C6-T-SYP	20 Feet	Class 6



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

[www.ledlightingsupply.com](http://www.ledlightingsupply.com) (888) 423-3191  
Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2220

# MLLG-POLE-WD-20-C5-T-SYP

20 Foot Wood Pole

Project Name \_\_\_\_\_



PRODUCT SPECIFICATIONS		
DIMENSIONS	Total Height	20 Feet
	Height Above Ground	16 Feet
	Outside Diameter	
	Weight Range	400-500 lbs
	Treatment	CCA
	Max Total Cross Arms	2
	Max Total Cross Arms Per Side	1
ANSI REQUIREMENTS	Max Attached Weight Per Cross Arm	240 lbs
	Min Circumference At Pole Top	19 inches
	Min Circumference 6 Feet From Butt	23 inches
	Min Diameter At Pole Top	6 inches
	Min Diameter 6 Feet From Butt	7.3 inches



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

[www.ledlightingsupply.com](http://www.ledlightingsupply.com) (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2220