

# MLLG-POLE-WD-40-C3-T-SYP

40 Foot Wood Pole

Project Name \_\_\_\_\_



### DETAILS

Southern Yellow Pine is species found south of the Mason-Dixon line and east of the Great Plains in the USA. It is known for its strength, stiffness, and density making it an ideal material for utility poles. It is effective in holding nails and other types of fasteners. The cellular structure makes it suitable for the pressure treatment process. Nearly 85% of all pressure-treated wood in the U.S. is southern yellow pine.

CCA Treated to Prevent Insect and Rot Damage

Up to 50+ Years Service Life

1-year warranty

Manufactured in the USA

OVERVIEW	
SKU:	MLLG-POLE-WD-40-C3-T-SYP
Warranty	1-year warranty
Species	
Treatment	CCA
ANSI Class	Class 3



## PRODUCT FAMILY MODELS

SKU	Total Height	ANSI Class
MLLG-POLE-WD-40-C1-T-SYP	40 Feet	Class 1
MLLG-POLE-WD-40-C2-T-SYP	40 Feet	Class 2
MLLG-POLE-WD-40-C3-T-SYP	40 Feet	Class 3
MLLG-POLE-WD-40-C4-T-SYP	40 Feet	Class 4
MLLG-POLE-WD-40-C5-T-SYP	40 Feet	Class 5



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

[www.ledlightingsupply.com](http://www.ledlightingsupply.com) (888) 423-3191  
Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2243

# MLLG-POLE-WD-40-C3-T-SYP

40 Foot Wood Pole

Project Name \_\_\_\_\_



## PRODUCT SPECIFICATIONS

<b>DIMENSIONS</b>	<b>Total Height</b>	40 Feet
	<b>Height Above Ground</b>	34 Feet
	<b>Outside Diameter</b>	
	<b>Weight Range</b>	1235-1460 lbs
	<b>Treatment</b>	CCA
	<b>Max Total Cross Arms</b>	2-4
	<b>Max Total Cross Arms Per Side</b>	1-2
<b>ANSI REQUIREMENTS</b>	<b>Max Attached Weight Per Cross Arm</b>	240 lbs
	<b>Min Circumference At Pole Top</b>	23 Inches
	<b>Min Circumference 6 Feet From Butt</b>	36 Inches
	<b>Min Diameter At Pole Top</b>	7.321 Inches
	<b>Min Diameter 6 Feet From Butt</b>	11.459 Inches



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

[www.ledlightingsupply.com](http://www.ledlightingsupply.com) (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2243