

MLLG-POLE-WD-55-C3-T-SYP

55 Foot Wood Pole

Project Name _____



DETAILS

Southern Yellow Pine is species found south of the Mason-Dixon line and east of the Great Plains in the USA. It is known for its strength, stiffness, and density making it an ideal material for utility poles. It is effective in holding nails and other types of fasteners. The cellular structure makes it suitable for the pressure treatment process. Nearly 85% of all pressure-treated wood in the U.S. is southern yellow pine.

CCA Treated to Prevent Insect and Rot Damage

Up to 50+ Years Service Life

1-year warranty

OVERVIEW	
SKU: MLLG-POLE-WD-55-C3-T-SYP	
Warranty	1-year warranty
Species	Southern Yellow Pine
Treatment	CCA
ANSI Class	Class 3



PRODUCT FAMILY MODELS

SKU	Total Height	ANSI Class
MLLG-POLE-WD-55-C3-T-SYP		Class 3
MLLG-POLE-WD-55-C4-T-SYP		Class 4
MLLG-POLE-WD-60-C1-T-SYP		Class 1
MLLG-POLE-WD-60-C2-T-SYP		Class 2
MLLG-POLE-WD-60-C3-T-SYP		Class 3
MLLG-POLE-WD-60-C4-T-SYP		Class 4



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

www.ledlightingsupply.com (888) 423-3191
Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2256

MLLG-POLE-WD-55-C3-T-SYP

55 Foot Wood Pole

Project Name _____



PRODUCT SPECIFICATIONS

DIMENSIONS	Total Height	
	Height Above Ground	
	Outside Diameter	
	Weight Range	
	Pole Height	55 ft
	Height Above Ground	47.5 ft
	Buried Depth Below Ground	7.5 ft
	Weight Range	2070-2440 lbs
	ANSI Class	3
	Species	Southern Yellow Pine
	Treatment	CCA
ANSI REQUIREMENTS	Max Total Cross Arms	2-4
	Max Total Cross Arms Per Side	1-2
	Max Attached Weight Per Cross Arm	240 lbs
	Min Circumference At Pole Top	23 Inches
	Min Circumference 6 Feet From Butt	40.5 Inches
	Min Diameter At Pole Top	7.321 Inches
	Min Diameter 6 Feet From Butt	12.8921 Inches
	Warranty	1 Year



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

www.ledlightingsupply.com (888) 423-3191

Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

WebID: 2256