LLS-WD-AWPFC-12/18/24/30-CC-PC

12 / 18 / 24 / 30 Watt Adjustable Full Cutoff Architectural LED Wall Pack

Project Name



DETAILS

12 | 18 | 24 | 30 Watt Adjustable and color adjustable [ColorTemperature] architectural full-cutoff LED wall pack has a full cut-off design for complete customizable illumination This fixture has a built-in photocell. It has a 0-90° adjustable head including a full cut-off design for complete customizable illumination. Its impact-resistant polycarbonate lens not only protects but also helps prevent glare.



Color Adjustable



Wattage Adjustable



Photocell

OVER'	VIEW S-WD-AWPFC-12/18/24/30-CC-PC
Watts	12 18 24 30
Lumens	1584 2376 3168 3960
Lumens Per Watt (Efficacy)	132
Color Temperature	3000K 4000K 5000K
Voltage	100V-277V



















AMP DRAW

Watts		Current Amp Draw		
Walls	120V	240V	277V	480V
12	0.10	0.05	0.04	0.03
18	0.15	0.08	0.06	0.04
24	0.20	0.10	0.09	0.05
30	0.25	0.13	0.11	0.06



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

LLS-WD-AWPFC-12/18/24/30-CC-PC

12 / 18 / 24 / 30 Watt Adjustable Full Cutoff Architectural LED Wall Pack



WebID: 2282

Project Name

PRODUC	T SPECIFICATIONS
Watts	12 18 24 30
Lumens	1584 2376 3168 3960
Color Temperature	3000K 4000K 5000K
CRI	70+
Replaces	100 Watt Metal Halide
Voltage	100-277
Power Factor (PF)	> .90
THD	< 20%
Dimming	1-10V
Power Factor (PF)	50-60Hz
IP Rating	IP65
Rated Life	50,000 (L70) hours
Certifications	Rebate Eligible UL Listed ROHS
Warranty	5
Mount	Wall
Color Options	Bronze



LLS-WD-AWPFC-12/18/24/30-CC-PC

12 / 18 / 24 / 30 Watt Adjustable Full Cutoff Architectural LED Wall Pack

Project Name



WebID: 2282

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
100	12	\$49.88	\$249.39
100	18	\$46.48	\$232.39
100	24	\$43.08	\$215.38
100	30	\$39.68	\$198.38

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-WD-AWPFC-12/18/24/30-CC-PC	12 18 24 30	1584 2376 3168 3960	132
LLS-WD-AWPFC-70-CC-PC-[C]	28 42 56 70	4760 6880 8600 11100	160

