LLS-WD-WPHM-70-[C]-PC

70 Watt Full Cutoff Half Moon LED Wall Pack

Project Name



DETAILS

70 Watt architectural full-cutoff LED wall pack is a commercial-grade outdoor fixture. This fixture has die-cast aluminum housing and impact-resistant polycarbonate lens. These wall packs have a built-in photocell.



Photocell

OVERVIEW		
SKU	LLS-WD-WPHM-70-[C]-PC	
Wattage	70	
Lumens	9445	
Lumens Per Watt (Efficacy)	135	
Color Temperature	4000K 5000K	
Voltage	100V-277V	



▶ PRODUCT DIMENSIONS

Product Dimensions	14 X 7.5 X 7.5 in
Product Weight	7.5 lbs



PRODUCT SKU VARIATIONS

SKU	Color Temp
LLS-WD-WPHM-70-4-PC	4000K
LLS-WD-WPHM-70-5-PC	5000K



LLS-WD-WPHM-70-[C]-PC

70 Watt Full Cutoff Half Moon LED Wall Pack

Project Name



WebID: 2289

PRODUCT SPECIFICATIONS		
	Wattage	70
	Lumens	9445
	Color Temperature	4000K 5000K
	CRI	70+
	Beam Angles	80°
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	> .90
	THD	< 20%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	Housing	Powder Coated Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-22°F to +113°F
	Rated Life	70,000 hours
	Certifications	Rebate Eligible UL Listed ROHS
	Warranty	5
	Mount	Wall
	Color Options	Bronze



LLS-WD-WPHM-70-[C]-PC

70 Watt Full Cutoff Half Moon LED Wall Pack

Project Name _____



WebID: 2289

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
250	70	\$102.02	\$510.12

PRODUCT FAMILY MODELS

SKU	Wattage	Lumens	Lumens/Watt
LLS-WD-WPHM-45-[C]-PC	45	6300	140
LLS-WD-WPHM-70-[C]-PC	70	9445	135

AMP DRAW

144-44		Current Amp Draw		
Wattage	120V	240V	277V	480V
70	0.58	0.29	0.25	0.15

