MLLG-E-LED-EXPLB-80-50-C1D2-HT

80 Watt Round High Temperature Explosion Proof LED Light

Project Name _



DETAILS

High Temp Explosion Proof Fixtures are ideal for heavy manufacturing and industrial facilities where ignitable gases may be present.

OVERVIEW

SKU	MLLG-E-LED-EXPLB-80-50-C1D2- HT
Watts	80
Lumens	8000
Lumens Per Watt (Efficacy)	100
Color Temperature	5000K
Voltage	120V



₽ PRODUCT DIMENSIONS

Product Weight	15 lbs











UL SPECS

UL 844 Hazardous Locations
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III
UL 1598 Suitable for Wet Locations
UL 1598A Marine Outside Type
ABS



MLLG-E-LED-EXPLB-80-50-C1D2-HT

80 Watt Round High Temperature Explosion Proof LED Light

Project Name _____



PRODUCT SPECIFICATIONS				
OPTICAL	Watts	80		
Lumens		8000		
	Color Temperature	5000K		
	CRI	70+		
	Replaces	250 Watt Metal Halide		
ELECTRICAL	Voltage	120		
	Power Factor (PF)	>.95		
	THD	< 10%		
	Dimming	No		
	Power Factor (PF)	50-60Hz		
CONSTRUCTION	IP Rating	IP66		
IK R		IK10		
	Rated Life	50,000 (L70) hours		
	Certifications	Rebate Eligible ETL Listed ROHS CB		
	Warranty	5		
	Mount	Yoke 3/4 in NPT Pendant		
	Color Options	Gray		



MLLG-E-LED-EXPLB-80-50-C1D2-HT

80 Watt Round High Temperature Explosion Proof LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	80	\$96.36	\$481.78

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLB-80-50-C1D2-HT	80	8000	100
MLLG-E-LED-EXPLB-100-50-C1D2-HT	100	10000	100
MLLG-E-LED-EXPLB-150-50-C1D2-HT	150	15000	100

