LLS-EXPLB-240-5-C1D2

240 Watt Round Explosion Proof LED Light

Project Name



DETAILS

240 Watt LED Explosion Proof Light - Class 1 Division 2 can be used indoors and outdoors. The fixture can be angled if required. Multiple mounting options are available: Surface | Wall | Trunnion | 3/4 in NPT Pendant. We offer a 10 year warranty on this product.

OVERVIEW	OVERVIEW		
sku	LLS-EXPLB-240-5-C1D2		
Watts	240		
Lumens	33600		
Lumens Per Watt (Efficacy)	140		
Color Temperature	5000K		
Voltage	100V-277V		

▶ PRODUCT DIMENSIONS

Product Dimensions	9.7 X 15 in
Product Weight	20 lbs

UL SPECS

Class 1 Division 2, Group A,B,C,D
Class 2, Division 1, Groups E,F,G
Class 2, Division 2, Groups F,G
Class 3
Class I, Zone 2, Group IIC
Zone 20 and Zone 21
Zone 22
UL844, Wet Locations (UL 1598 / UL1598A)
CSA, ATEX, IECEX















LLS-EXPLB-240-5-C1D2

240 Watt Round Explosion Proof LED Light

Project Name



WebID: 2312

PRODUCT SPECIFICATIONS		
	Watts	240
	Lumens	33600
	Color Temperature	5000K
	CRI	70+
	Replaces	1000 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	>.90
	THD	< 10%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	IP Rating	IP66
	IK Rating	IK10
	Operating Temperature	-40°F to 149°F
	Rated Life	150,000 (L70) hours
	Certifications	Rebate Eligible UL Listed ROHS CB
	Warranty	5 or 10
	Mount	Pendant Surface Wall Trunnion
	Color Options	Gray



LLS-EXPLB-240-5-C1D2

240 Watt Round Explosion Proof LED Light

Project Name



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
1000	240	\$430.77	\$2,153.84

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-EXPLB-100-5-C1D2	100	14000	140
LLS-EXPLB-150-5-C1D2	150	21000	140
LLS-EXPLB-240-5-C1D2	240	33600	140

