LLS-AG-SLH-AC-60-40-T3

60 Watt Hybrid Solar Area Light

Project Name _____



DETAILS

60 Watt High-Performance LED Hybrid Solar / 100V-277V Street Light. This fixture can work from a solar battery source or a direct wired connection. A great option when you have a wired source but also need a battery backup option!

Motion Sensor

OVERVIEW			
SKU	LLS-AG-SLH-AC-60-40-T3		
Watts	60		
Lumens	12000		
Lumens Per Watt (Efficacy)	200		
Color Temperature	4000K		
Voltage	100V-277V		

₽ PRODUCT DIMENSIONS

Product Weight 44 lbs

AMP DRAW

	Current Amp Draw				
Watts	120V	240V	277V	480V	
60	0.50	0.25	0.22	0.13	







LLS-AG-SLH-AC-60-40-T3

60 Watt Hybrid Solar Area Light

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	ts 60	
	Lumens	12000	
	Color Temperature 4000K		
	CRI 70+ Beam Angles Type 3		
	Replaces	250 Watt Metal Halide	
ELECTRICAL	Voltage	100-277	
	Dimming	No	
CONSTRUCTION	Housing Aluminum Alloy Monocrystalline Solar Panel		
	IP Rating	IP65	
	Operating Temperature	0°F to 122°F	
	Rated Life	100,000 (L70) hours	
	Certifications	ROHS	
	Warranty	Fixture: 5 years Battery: 3 years	
	Mount	Slip Fitter	



LLS-AG-SLH-AC-60-40-T3

60 Watt Hybrid Solar Area Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
250	60	\$107.69	\$538.46

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-AG-SLH-AC-40-40-T3	40	8000	200
LLS-AG-SLH-AC-60-40-T3	60	12000	200
LLS-AG-SLH-AC-80-40-T3	80	16000	200
LLS-AG-SLH-AC-100-40-T3	100	20000	200

