LLS-AL-HBLIN6A-100/130/160-5

100 / 130 / 160 Watt Adjustable Linear LED High Bay

Project Name



DETAILS

100 / 130 / 160 Watt Adjustable Linear LED High Bay provides an exceptional lighting solution, combining efficiency and durability for various industrial and commercial applications



Wattage Adjustable



Emergency Backup Battery



Motion Sensor

OVERVIEW

LLS-AL-HBLIN6A-100/130/160-5
100 130 160
15500 20150 24800
155
5000K
100V-277V



Product Dimensions	14.9 x 9.8 x 2.9 in
Product Weight	5 lbs
Cord Length	No Cord



Wattago		Current An	np Draw	
Wattage	120V	240V	277V	480V
100	0.83	0.42	0.36	0.21
130	1.08	0.54	0.47	0.27
160	1.33	0.67	0.58	0.33















Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

LLS-AL-HBLIN6A-100/130/160-5

100 / 130 / 160 Watt Adjustable Linear LED High Bay

Project Name



PRODUCT SPECIFICATIONS					
	Wattage	100 130 160			
	Lumens	15500 20150 24800			
	Color Temperature	5000K			
	CRI	80+			
OPTICAL	Beam Angles	90°			
	Replaces	250 Watt Metal Halide 400 Watt Metal Halide			
	Voltage	100-277			
	Power Factor (PF)	.90			
	THD	20% Max			
	Dimming	0-10V			
ELECTRICAL	Surge Protection	6kV line-line, 6kV line-earth			
	Power Factor (PF)	50 / 60 hz			
	Housing	Die-Cast Aluminum			
	IP Rating	IP20			
CONSTRUCTION	IK Rating	IK10			
	Operating Temperature	-40°F to 122°F			
	Rated Life	170,000 (L70) hours			
	Certifications	Rebate Eligible UL Listed ROHS			
	Warranty	5			
	Mount	Chain-Cable (std) Pendant Surface			
	Color Options	White			



LLS-AL-HBLIN6A-100/130/160-5

100 / 130 / 160 Watt Adjustable Linear LED High Bay

Project Name



WebID: 2346

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
400	100	\$170.04	\$850.20
400	130	\$153.04	\$765.18
400	160	\$136.03	\$680.16

