LLS-X-CPS-63A-CC-[C]

30 / 45 / 63 Watt Adjustable LED Canopy Light

Project Name



DETAILS

LED Canopy Lights are commercial outdoor light fixtures commonly used in parking garages or covered pedestrian ways. The mounting heights are lower, they tend to have very wide beam angles. This ensures the light can reach as much area as possible.



Color Adjustable



Wattage Adjustable

OVERVI	OVERVIEW	
SKU	LLS-X-CPS-63A-CC-[C]	
Wattage	30 45 63	
Lumens	4000 6000 8500	
Lumens Per Watt (Efficacy)	135	
Color Temperature	4000K 5000K	
Voltage	100V-277V	







SKU	Fixture Color
LLS-X-CPS-63A-CC-B	Bronze
LLS-X-CPS-63A-CC-W	White

















Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

LLS-X-CPS-63A-CC-[C]

30 / 45 / 63 Watt Adjustable LED Canopy Light

Project Name



WebID: 2478

PRODUCT SPECIFICATIONS		
	Wattage	30 45 63
	Lumens	4000 6000 8500
	Color Temperature	4000K 5000K
	CRI	80+
	Beam Angles	140°
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Dimming	No
	Power Factor (PF)	50-60Hz
	Housing	Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-40°F to +113°F
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible UL Listed ROHS
	Warranty	5
	Mount	Pendant Surface
	Color Options	Bronze White



LLS-X-CPS-63A-CC-[C]

30 / 45 / 63 Watt Adjustable LED Canopy Light

Project Name



♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
250	30	\$124.70	\$623.48
250	45	\$116.19	\$580.97
250	63	\$105.99	\$529.96

AMP DRAW

Wattaga		Current Amp Draw		
Wattage	120V	240V	277V	480V
30	0.25	0.13	0.11	0.06
45	0.38	0.19	0.16	0.09
63	0.53	0.26	0.23	0.13

