### LLS-X-FLD6-108A-CC-[Mount]-PC

63 / 90 / 108 Watt Adjustable LED Flood Light

Project Name



#### **DETAILS**

LED Lighting Supply Commercial LED Flood Lights are a versatile and energy-efficient fixture that is used to provide illumination and security lighting in outdoor spaces. They can be used in locations such as parking lots and roadways. They are typically mounted on poles, walls, and roofs. LED Sports Flood Lights can be used for sports courts and tennis courts.



Color Adjustable



Wattage Adjustable



Photocell

•	OVERVIEW  LLS-X-FLD6-108A-CC-[Mount]-PC	
Watts	63   90   108	
Lumens	9700   14000   17200	
Lumens Per Watt (Efficacy)	155	
Color Temperature	3000K   4000K   5000K	
Voltage	100V-277V	







SKU	Mounting
LLS-X-FLD6-108A-CC-SF-PC	Slip Fitter
LLS-X-FLD6-108A-CC-YM-PC	Yoke

















Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

# LLS-X-FLD6-108A-CC-[Mount]-PC

63 / 90 / 108 Watt Adjustable LED Flood Light

Project Name



PRODUCT SPECIFICATIONS		
	Watts	63   90   108
	Lumens	9700   14000   17200
	Color Temperature	3000K   4000K   5000K
	CRI	80+
	Beam Angles	120°
	Replaces	250 Watt Metal Halide   400 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	.9
	THD	15%
	Dimming	No
	Power Factor (PF)	50-60Hz
	Housing	Die-Cast Aluminium
	IP Rating	IP65
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible   UL Listed   ROHS
	Warranty	5
	Mount	Yoke   Slip Fitter
	Color Options	Bronze



# LLS-X-FLD6-108A-CC-[Mount]-PC

63 / 90 / 108 Watt Adjustable LED Flood Light

Project Name



### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	63	\$191.01	\$955.06
400	90	\$175.71	\$878.54
400	108	\$165.51	\$827.53

### **PRODUCT FAMILY MODELS**

SKU	Watts	Lumens	Lumens/Watt
LLS-X-FLD6-17/25/30-CC-[Mount]	17 25 30	2890 4250 5100	153
LLS-X-FLD6-36/50/63-CC-[Mount]	36 50 63	5580 7750 9700	153
LLS-X-FLD6-108A-CC-[Mount]-PC	63 90 108	9700 14000 17200	155

### AMP DRAW

Watts		Current Amp Draw		
watts	120V	240V	277V	480V
63	0.53	0.26	0.23	0.13
90	0.75	0.38	0.32	0.19
108	0.90	0.45	0.39	0.23

