LLS-X-WPFC-63A-CC-PC

30 / 45 / 63 Watt Adjustable Full Cutoff LED Wall Pack

Project Name



DETAILS

LED wall packs are wall-mounted outdoor lighting fixtures that provide high-quality energy-efficient lighting for commercial and industrial applications. These outdoor lights are ideal to illuminate building exteriors, pathways, parking lots, and other outdoor spaces. Some models come equipped with a photocell to automatically turn the fixture on at dusk and off at dawn.



Color Adjustable



Wattage Adjustable



Photocell

OVERV	OVERVIEW	
SKU	LLS-X-WPFC-63A-CC-PC	
Wattage	30 45 63	
Lumens	4500 7500 9800	
Lumens Per Watt (Efficacy)	140	
Color Temperature	3000K 4000K 5000K	
Voltage	100V-277V	







Wattaga		Current Amp Draw		
Wattage	120V	240V	277V	480V
30	0.25	0.13	0.11	0.06
45	0.38	0.19	0.16	0.09
63	0.53	0.26	0.23	0.13




















Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

LLS-X-WPFC-63A-CC-PC

30 / 45 / 63 Watt Adjustable Full Cutoff LED Wall Pack

Project Name



PRODUCT SPECIFICATIONS		
	Wattage	30 45 63
	Lumens	4500 7500 9800
	Color Temperature	3000K 4000K 5000K
	CRI	70+
	Replaces	250 Watt Metal Halide
	Voltage	100-277
	Power Factor (PF)	> .9
	THD	< 20%
	Dimming	No
	Surge Protection	4KV
	Power Factor (PF)	50-60Hz
	Housing	Powder Coated Die-Cast Aluminum
	IP Rating	IP65
	Operating Temperature	-40°F to +113°F
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible UL Listed ROHS
	Warranty	5
	Mount	Wall
	Color Options	Bronze



LLS-X-WPFC-63A-CC-PC

30 / 45 / 63 Watt Adjustable Full Cutoff LED Wall Pack

Project Name



WebID: 2485

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Wattage	LED Wattage	1 Year Energy Savings	5 Year Energy Savings
250	30	\$124.70	\$623.48
250	45	\$116.19	\$580.97
250	63	\$105.99	\$529.96

PRODUCT FAMILY MODELS

SKU	Wattage	Lumens	Lumens/Watt
LLS-X-WPFC-63A-CC-PC	30 45 63	4500 7500 9800	140
LLS-X-WPFC-90A-CC-PC-[COLOR]	45 63 90	7200 10000 14000	150
LLS-X-WPFC-125A-CC-PC-[COLOR]	76 105 125	12000 16800 19700	150

