### MLLG-E-LED-EXPLB-150-50-C1D2NSF

150 Watt Round Explosion Proof LED Light

Droject Name			



#### **DETAILS**

Rated to meet National Sanitation Foundation (NSF) standards and provide Class I, Division 2 (C1D2) explosion-proof protection, these fixtures are ideal for environments with stringent safety and sanitation requirements.



NSF Rated Food Grade

OVERVIEW sku MLLG-E-LED	-EXPLB-150-50-C1D2NSF
Watts	150
Lumens	21000
Lumens Per Watt (Efficacy)	140
Color Temperature	5000K
Voltage	100V-277V



Product Dimensions	12.6 in D X 9.2 in H
Product Weight	22.60 lbs



© UL SPECS
JL 844 Hazardous Locations
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III
JL 1598 Suitable for Wet Locations
JL 1598A Marine Outside Type
ABS
NSF















WebID: 2492



Product design upgrades may result in specification changes without notice. Speak to a Product Specialist for the latest information.

## MLLG-E-LED-EXPLB-150-50-C1D2NSF

150 Watt Round Explosion Proof LED Light

Project Name



PRODUCT SPECIFICATIONS			
	Watts	150	
	Lumens	21000	
	Color Temperature	5000K	
	CRI	80+	
	Replaces	400 Watt Metal Halide	
	Voltage	100-277	
	Power Factor (PF)	>.95	
	Dimming	1-10V	
	Power Factor (PF)	50-60Hz	
	IP Rating	IP66	
	IK Rating	IK10	
	Rated Life	50,000 (L70) hours	
	Certifications	Rebate Eligible   ETL Listed   NSF Certified   ROHS   CB	
	Warranty	5	
	Mount	3/4 in NPT Pendant	



# MLLG-E-LED-EXPLB-150-50-C1D2NSF

150 Watt Round Explosion Proof LED Light

Project Name



### **♦ ENERGY SAVINGS**

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	150	\$141.70	\$708.50

### **○** PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-E-LED-EXPLB-60-50-C1D2NSF	60	8400	140
MLLG-E-LED-EXPLB-100-50-C1D2NSF	100	14000	140
MLLG-E-LED-EXPLB-150-50-C1D2NSF	150	21000	140
MLLG-E-LED-EXPLB-200-50-C1D2NSF	200	28000	140

