LLS-STRL-50-5-T3

50 Watt LED Street Light

Project Name _____



DETAILS

Our LED Street Lights are pole-mounted light fixtures designed to light up roadways and urban streets and are a common outdoor lighting solution. They are sometimes referred to as cobra head lights. LED Street lights are mounted on the top of a light pole, and there is usually one light per pole. The light has optics that allow it to distribute the light on the roadway. Streetlights are sometimes equipped with a photocell that turns the lights on at dusk and off at dawn. LED Streetlights fixtures can easily replace high-pressure sodium lights and metal halide road lighting.



OVERVIEW				
LLS-STRL-50-5-T3				
50				
8000				
160				
3000K 4000K 5000K				
100V-277V				

₽ PRODUCT DIMENSIONS

Product Weight 12.5 lbs



		Curre	nt Amp Draw	
Watts	120V	240V	277V	480V
50	0.42	0.21	0.18	0.10





LLS-STRL-50-5-T3

50 Watt LED Street Light

Project Name _____



PRODUCT SPECIFICATIONS					
OPTICAL	Watts	50			
	Lumens	8000			
	Color Temperature	3000K 4000K 5000K			
	CRI	70+			
	Beam Angles	Type 3 std, (2, 4, 5 optional)			
	Replaces	150 Watt Metal Halide			
ELECTRICAL	Voltage	100-277			
	Dimming	1-10V			
	Surge Protection	4kV line-line, 6kV line-earth			
	Power Factor (PF)	50-60Hz			
CONSTRUCTION	Housing	Aluminum Alloy			
	IP Rating	IP66			
	IK Rating	IK09			
Operating Temperat		-22°F to +122°F			
	Rated Life	131,000 (L70) hours			
	Certifications	Rebate Eligible ETL Listed ROHS			
	Warranty	5			
	Mount	Pole			
	Color Options	Black			



LLS-STRL-50-5-T3

50 Watt LED Street Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
150	50	\$56.68	\$283.40

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-STRL-30-5-T3	30	4800	160
LLS-STRL-50-5-T3	50	8000	160
LLS-STRL-70-5-T3	70	12000	171
LLS-STRL-90-5-T3	90	14400	160
LLS-STRL-120-5-T3	120	19200	160
LLS-STRL-150-5-T3	150	24000	160
LLS-STRL-180-5-T3	180	28800	160
LLS-STRL-200-5-T3	200	32000	160

