### LLS-STRL-150-5-T3

150 Watt LED Street Light

Project Name \_\_\_\_\_



#### **DETAILS**

Our LED Street Lights are pole-mounted light fixtures designed to light up roadways and urban streets and are a common outdoor lighting solution. They are sometimes referred to as cobra head lights. LED Street lights are mounted on the top of a light pole, and there is usually one light per pole. The light has optics that allow it to distribute the light on the roadway. Streetlights are sometimes equipped with a photocell that turns the lights on at dusk and off at dawn. LED Streetlights fixtures can easily replace high-pressure sodium lights and metal halide road lighting.



	w
OVERVIE	м

SKU	LLS-STRL-150-5-T3
Watts	150
Lumens	24000
Lumens Per Watt (Efficacy)	160
Color Temperature	3000K   4000K   5000K
Voltage	100V-277V

### **▶** PRODUCT DIMENSIONS

Product Weight 19.5 lbs



	Current Amp Draw				
Watts	120V	240V	277V	480V	
150	1.25	0.63	0.54	0.31	





# LLS-STRL-150-5-T3

150 Watt LED Street Light

Project Name \_\_\_\_\_



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	150	
	Lumens	24000	
	Color Temperature	3000K   4000K   5000K	
	CRI	70+	
	Beam Angles (Alt)	Type 3 std, (2, 4, 5 optional)	
	Optics	Tempered Glass with Polycarbonate Lens	
	Replaces 400 Watt Metal Halide		
ELECTRICAL	Voltage	100-277	
	Dimming	1-10V	
	Surge Protection	5kV line-line,10kV line-earth	
	Power Factor (PF)	50-60Hz	
CONSTRUCTION	Housing	Aluminum Alloy	
	IP Rating	IP66	
	IK Rating	IK09	
	Operating Temperature	-22°F to +122°F	
	Rated Life	131,000 (L70) hours	
	Certifications	Rebate Eligible   ETL Listed   ROHS	
	Warranty	5	
	Mount	Pole	
	Color Options	Black	



## LLS-STRL-150-5-T3

150 Watt LED Street Light

Project Name \_\_\_\_\_



### **4** ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	150	\$141.70	\$708.50

## **PRODUCT FAMILY MODELS**

SKU	Watts	Lumens	Lumens/Watt
LLS-STRL-30-5-T3	30	4800	160
LLS-STRL-50-5-T3	50	8000	160
LLS-STRL-70-5-T3	70	12000	171
LLS-STRL-90-5-T3	90	14400	160
LLS-STRL-120-5-T3	120	19200	160
LLS-STRL-150-5-T3	150	24000	160
LLS-STRL-180-5-T3	180	28800	160
LLS-STRL-200-5-T3	200	32000	160

