### LLS-STRL-180-5-T3

180 Watt LED Street Light

Project Name \_\_\_\_\_



#### **DETAILS**

Our LED Street Lights are pole-mounted light fixtures designed to light up roadways and urban streets and are a common outdoor lighting solution. They are sometimes referred to as cobra head lights. LED Street lights are mounted on the top of a light pole, and there is usually one light per pole. The light has optics that allow it to distribute the light on the roadway. Streetlights are sometimes equipped with a photocell that turns the lights on at dusk and off at dawn. LED Streetlights fixtures can easily replace high-pressure sodium lights and metal halide road lighting.



OVERVIEW			
SKU	LLS-STRL-180-5-T3		
Watts	180		
Lumens	28800		
Lumens Per Watt (Efficacy)	160		
Color Temperature	3000K   4000K   5000K		
Voltage	100V-277V		

### **₽** PRODUCT DIMENSIONS

**Product Weight** 19.5 lbs



	Current Amp Draw			
Watts	120V	240V	277V	480V
180	1.50	0.75	0.65	0.38





# LLS-STRL-180-5-T3

180 Watt LED Street Light

Project Name \_\_\_\_\_



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	180	
	Lumens	28800	
	Color Temperature	3000Κ   4000Κ   5000Κ	
	CRI	70+	
	Beam Angles	Type 3 std, (2, 4, 5 optional)	
	Replaces	400 Watt Metal Halide   750 Watt Metal Halide	
ELECTRICAL	Voltage	100-277	
	Dimming	1-10V	
	Surge Protection	5kV line-line,10kV line-earth	
	Power Factor (PF)	50-60Hz	
CONSTRUCTION	Housing	Aluminum Alloy	
	IP Rating	IP66	
	IK Rating	IK09	
	Operating Temperature	-22°F to +122°F	
	Rated Life	131,000 (L70) hours	
	Certifications	Rebate Eligible   ETL Listed   ROHS	
	Warranty	5	
	Mount	Pole	
	Color Options	Black	



# LLS-STRL-180-5-T3

180 Watt LED Street Light

Project Name \_\_\_\_\_



### **4** ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
750	180	\$323.08	\$1,615.38

## **PRODUCT FAMILY MODELS**

SKU	Watts	Lumens	Lumens/Watt
LLS-STRL-30-5-T3	30	4800	160
LLS-STRL-50-5-T3	50	8000	160
LLS-STRL-70-5-T3	70	12000	171
LLS-STRL-90-5-T3	90	14400	160
LLS-STRL-120-5-T3	120	19200	160
LLS-STRL-150-5-T3	150	24000	160
LLS-STRL-180-5-T3	180	28800	160
LLS-STRL-200-5-T3	200	32000	160



Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060