MLLG-LN-LED-EXIT2-2L-B

5 Watt Emergency Light and Exit Sign

Project Name _____



DETAILS

Emergency exit signs provide clear, illuminated directions to the nearest exit. LED exit signs are energy efficient and provide high visibility. They are equipped with a battery backup to stay lit for up to 90 minutes in case of an interrupted power supply.

OVERVIEW			
SKU	MLLG-LN-LED-EXIT2-2L-B		
Watts	5		
Lumens			
Lumens Per Watt (Efficacy)	0		
Color Temperature			
Voltage	100V-277V		



₽ PRODUCT DIMENSIONS

AMP DRAW

Current Amp Draw				
Watts	120V	240V	277V	480V
5	0.04	0.02	0.02	0.01





MLLG-LN-LED-EXIT2-2L-B

5 Watt Emergency Light and Exit Sign

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	5	
	Beam Angles	120°	
	Replaces	36W CFL	
ELECTRICAL	Voltage	100-277	
	Power Factor (PF)	> .90	
	THD	< 20%	
	Dimming	No	
	Power Factor (PF)	50-60Hz	
CONSTRUCTION	Housing	Injection-Molded Thermoplastic ABS	
	Operating Temperature	32°F to +104°F	
	Rated Life	50,000 hours	
	Certifications	UL Listed ROHS	
	Warranty	3	
	Mount	Surface	
	Color Options	Black	



MLLG-LN-LED-EXIT2-2L-B

5 Watt Emergency Light and Exit Sign

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
36	5	\$17.57	\$87.85

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-WD-LED-BARN-45-50	45	6300	140
LLS-X-STL-4-50A-CC	30 40 50	4200 5300 6500	133
MLLG-AL-LED-LIN-SWL-44-CC-MS	22 28 36 44	3102 3948 5076 6204	141
MLLG-LN-LED-EXIT2-2L	2.4		NaN
LLS-HD-HM3-450-50-[V]-T5	450	69750	155
LLS-HD-HM3-600-50-[V]-T5	600	90000	150
LLS-HD-HM3-750-50-[V]-T5	750	112500	150
MLLG-YA-LED-PT-100-CC	60 80 100	7800 10400 13000	130
LLS-LN-4FT-T8-18-5-C-25P	18	2160	120
LLS-LN-8FT-T8-36-5-F-25P	36	4320	120
LLS-LN-8FT-T8-44-65-C-25P	44	5700	130

