LLS-DG-CAN-35-40-20G-WH

35 Watt Detention Grade LED Canopy Light

Project Name _____



DETAILS

Our detention-grade fixtures are typically constructed from 16 to 20-gauge cold-rolled steel and secured with tamper-proof fasteners. With IK08 to IK10 impact ratings, these fixtures are designed to resist vandalism and prevent unauthorized access. Common applications include prisons, jails, behavioral health facilities, and other high-traffic public areas.

OVERVIEW				
SKU	LLS-DG-CAN-35-40-20G-WH			
Watts	35			
Lumens	5000			
Lumens Per Watt (Efficacy)	143			
Color Temperature	4000K			
Voltage	100V-277V			



₽ PRODUCT DIMENSIONS

AMP DRAW

	Current Amp Draw			
Watts ₁₂₀ V	120V	240V	277V	480V
35	0.29	0.15	0.13	0.07





LLS-DG-CAN-35-40-20G-WH

35 Watt Detention Grade LED Canopy Light

Project Name _____



PRODUCT SPECIFICATIONS					
OPTICAL	Watts	35			
	Lumens	5000			
	Color Temperature	4000K			
	CRI	80+			
	Replaces	150 Watt Metal Halide			
ELECTRICAL	Voltage	100-277			
	Power Factor (PF)	>0.9			
	Dimming	0-10V			
	Power Factor (PF)	50 / 60Hz			
CONSTRUCTION	Housing	20-Gauge Cold Roll Steel			
	Fasteners	Torx Screws			
	Operating Temperature	-4°F to 140°F			
	Rated Life	100,000 (L70) hours			
	Certifications	Rebate Eligible ETL Listed BAA-TAA			
	Warranty	5			
	Mount	Surface			
	Color Options	Black Bronze Silver White			



LLS-DG-CAN-35-40-20G-WH

35 Watt Detention Grade LED Canopy Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
150	35	\$65.18	\$325.91

