LLS-DG-2X2S-45-40-16G-PA13-P16

45 Watt Detention Grade Surface Mount 2x2 LED Panel

Project Name _____



DETAILS

Our detention-grade fixtures are typically constructed from 16 to 20-gauge cold-rolled steel and secured with tamper-proof fasteners. With IK08 to IK10 impact ratings, these fixtures are designed to resist vandalism and prevent unauthorized access. Common applications include prisons, jails, behavioral health facilities, and other high-traffic public areas.

OVERVIEW			
sku	LLS-DG-2X2S-45-40-16G-PA13- P16		
Watts	45		
Lumens	7000		
Lumens Per Watt (Efficacy)	156		
Color Temperature	4000K		
Voltage	100V-277V		



₽ PRODUCT DIMENSIONS

AMP DRAW

	Current Amp Draw			
Watts	120V	240V	277V	480V
45	0.38	0.19	0.16	0.09













LLS-DG-2X2S-45-40-16G-PA13-P16

45 Watt Detention Grade Surface Mount 2x2 LED Panel

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	45	
	Lumens	7000	
	Color Temperature	4000K	
	CRI	80+	
	Replaces	150 Watt Metal Halide	
ELECTRICAL	Voltage	100-277	
	Power Factor (PF)	>0.9	
	Dimming	0-10V	
	Power Factor (PF)	50 / 60Hz	
CONSTRUCTION	Housing	16-Gauge Cold Roll Steel	
	Fasteners	Tamper-Resistant T25 TORX Screws	
	IK Rating	IK07	
	Operating Temperature	-4°F to 140°F	
	Rated Life	100,000 (L70) hours	
	Certifications	Rebate Eligible ETL Listed BAA-TAA	
	Warranty	5	
	Mount	Surface	
	Color Options	White	



Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060

LLS-DG-2X2S-45-40-16G-PA13-P16

45 Watt Detention Grade Surface Mount 2x2 LED Panel

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
150	45	\$59.51	\$297.57

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-DG-1X4S-45-40-16G-PA13-P16	45	7000	156
LLS-DG-2X2S-45-40-16G-PA13-P16	45	7000	156
LLS-DG-2X4S-80-40-16G-PA13-P16	80	12000	150

