LLS-DG-2X4S-80-40-16G-PA13-P16

80 Watt Detention Grade Surface Mount 2x4 LED Panel

Project Name _____



DETAILS

Our detention-grade fixtures are typically constructed from 16 to 20-gauge cold-rolled steel and secured with tamper-proof fasteners. With IK08 to IK10 impact ratings, these fixtures are designed to resist vandalism and prevent unauthorized access. Common applications include prisons, jails, behavioral health facilities, and other high-traffic public areas.

OVERVIEW		
sku	LLS-DG-2X4S-80-40-16G-PA13- P16	
Watts	80	
Lumens	12000	
Lumens Per Watt (Efficacy)	150	
Color Temperature	4000K	
Voltage	100V-277V	



₽ PRODUCT DIMENSIONS

AMP DRAW

		Curre	nt Amp Draw	
Watts	120V	240V	277V	480V
80	0.67	0.33	0.29	0.17













LLS-DG-2X4S-80-40-16G-PA13-P16

80 Watt Detention Grade Surface Mount 2x4 LED Panel

Project Name _____



PRODUCT SPECIFICATIONS			
OPTICAL	Watts	80	
	Lumens	12000	
	Color Temperature	4000K	
	CRI	80+	
	Replaces	400 Watt Metal Halide	
ELECTRICAL	Voltage	100-277	
	Power Factor (PF)	>0.9	
	Dimming	0-10V	
	Power Factor (PF)	50 / 60Hz	
CONSTRUCTION	Housing	16-Gauge Cold Roll Steel	
	Fasteners	Tamper-Resistant T25 TORX Screws	
	IK Rating	IK07	
Operating Temperatu		-4°F to 140°F	
	Rated Life	100,000 (L70) hours	
	Certifications	Rebate Eligible ETL Listed BAA-TAA	
	Warranty	5	
	Mount	Surface	
	Color Options	White	



LLS-DG-2X4S-80-40-16G-PA13-P16

80 Watt Detention Grade Surface Mount 2x4 LED Panel

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	80	\$181.38	\$906.88

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-DG-1X4S-45-40-16G-PA13-P16	45	7000	156
LLS-DG-2X2S-45-40-16G-PA13-P16	45	7000	156
LLS-DG-2X4S-80-40-16G-PA13-P16	80	12000	150

