MLLG-LED-EXPLR2-40-50-C1D2

40 Watt Explosion Proof Vapor Tight LED Light

Project Name



DETAILS

30 Watt LED Explosion Proof - Class 1 Division 2 light is a compact vapor-proof style fixture that replaces fluorescent lighting for hazardous locations. This is a polycarbonate fixture with a clear polycarbonate frosted lens. Emergency Battery Backup (EMB) is an option.

OVERVIEW KU MLLG-LED-EXPLR2-40-50-C1D2		
Watts	40	
Lumens	5600	
Lumens Per Watt (Efficacy)	140	
Color Temperature	5000K	
Voltage	100V-277V 277V-480V Optional	



▶ PRODUCT DIMENSIONS

Product Dimensions	28 in X 8.6 in X 5.3 in	
Product Weight	11 lbs	



UL SPECS





MLLG-LED-EXPLR2-40-50-C1D2

40 Watt Explosion Proof Vapor Tight LED Light

Project Name



WebID: 2659

PRODUCT SPECIFICATIONS		
	Watts	40
	Lumens	5600
	Color Temperature	5000K
	CRI	80+
	Replaces	150 Watt Metal Halide
	Voltage	100-277 277-480 Optional
	Power Factor (PF)	>.95
	THD	< 10%
	Dimming	1-10V
	Power Factor (PF)	50-60Hz
	IP Rating	IP66
	IK Rating	IK10
	Rated Life	50,000 (L70) hours
	Certifications	Rebate Eligible ETL Listed ROHS
	Warranty	5
	Mount	Surface



MLLG-LED-EXPLR2-40-50-C1D2

40 Watt Explosion Proof Vapor Tight LED Light

Project Name



WebID: 2659

♦ ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
150	40	\$62.35	\$311.74

PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
MLLG-LED-EXPLR2-20-50-C1D2	20	2800	140
MLLG-LED-EXPLR2-30-50-C1D2	30	4200	140
MLLG-LED-EXPLR2-40-50-C1D2	40	5600	140
MLLG-LED-EXPLR4-50-50-C1D2	50	7000	140
MLLG-LED-EXPLR4-60-50-C1D2	60	8400	140

