MLLG-E-EXPLS2-150-50-C1D1

150 Watt Round Explosion Proof LED Light

Project Name _____



DETAILS

EXPLS2 is a robust explosion proof C1D1 fixture that produces 21000 lumens, our standard unit allows mounting with either 3/4 inch NPT conduit or a yoke mount, the design also includes an internal junction box for ease of install on new or exisiting construction.

OVERVIEW			
SKU	MLLG-E-EXPLS2-150-50-C1D1		
Watts	150		
Lumens	21000		
Lumens Per Watt (Efficacy)	140		
Color Temperature	5000K		
Voltage	100V-277V		

₽ PRODUCT DIMENSIONS

Product Weight 45.3 lbs



UL 844 Hazardous Locations

Class I, Division 1, Groups B, C, D

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

UL 1598 Suitable for Wet Locations

UL 1598A Marine Outside Type

ABS















MLLG-E-EXPLS2-150-50-C1D1

150 Watt Round Explosion Proof LED Light

Project Name _____



PRODUCT SPECIFICATIONS				
OPTICAL	Watts	150		
	Lumens	21000		
	Color Temperature	5000K		
	CRI	70+		
	Replaces	400 Watt Metal Halide		
ELECTRICAL	Voltage	100-277		
	Power Factor (PF)	>.95		
	THD	< 10%		
	Power Factor (PF)	50-60Hz		
CONSTRUCTION	IP Rating	IP66		
	IK Rating	IK10		
	Rated Life	50,000 (L70) hours		
	Certifications	Rebate Eligible UL Listed		
	Warranty	5		
	Mount	Yoke 3/4 in NPT Pendant		
	Color Options	Gray		



MLLG-E-EXPLS2-150-50-C1D1

150 Watt Round Explosion Proof LED Light

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	150	\$141.70	\$708.50

