LLS-X-HB9-150A-CC-[C]

80 / 100 / 150 Watt Adjustable LED UFO High Bay

Project Name.



DETAILS

Our commercial and industrial project partners rely on this adjustable UFO high bay fixture to enhance visibility and amplify worker safety. Engineered with advanced CRI, this fixture reduces the risk of worker injury in warehouses and factories. It can be equipped with motion sensor technology in high foot traffic zones, providing enhanced energy efficiency benefits while minimizing facility maintenance costs. If mitigating safety hazards and maximizing productivity are top-of-mind, this fixture is the ideal solution.

OVERVIEW	
SKU	LLS-X-HB9-150A-CC-[C]
Watts	80 100 150
Lumens	12000 15000 22500
Lumens Per Watt (Efficacy)	150
Color Temperature	4000K 5000K
Voltage	100V-277V



₽ PRODUCT DIMENSIONS

Product Weight 4.5 lbs














PRODUCT SKU VARIATIONS

SKU	Fixture Color
LLS-X-HB9-150A-CC	Black
LLS-X-HB9-150A-CC-W	White





LLS-X-HB9-150A-CC-[C]

80 / 100 / 150 Watt Adjustable LED UFO High Bay

Project Name _____



PRODUCT SPECIFICATIONS		
OPTICAL	Watts	80 100 150
	Lumens	12000 15000 22500
	Color Temperature	4000K 5000K
	CRI	80+
	Replaces	250 Watt Metal Halide 400 Watt Metal Halide
ELECTRICAL	Voltage	100-277
	Power Factor (PF)	.90
	Dimming	0-10V
	Power Factor (PF)	50 / 60 hz
CONSTRUCTION	IP Rating	IP65
	Rated Life	50,000 (L70) hours
	Certifications	DLC Premium UL Listed ROHS
	Warranty	5
	Mount	Eye-Hook (std) Surface
	Color Options	Black White



LLS-X-HB9-150A-CC-[C]

80 / 100 / 150 Watt Adjustable LED UFO High Bay

Project Name _____



4 ENERGY SAVINGS

Based on 12 hours / day and \$0.13 kWh - eia.gov national average(2025)

Metal Halide Watts	LED Watts	1 Year Energy Savings	5 Year Energy Savings
400	80	\$181.38	\$906.88
400	100	\$170.04	\$850.20
400	150	\$141.70	\$708.50

□ PRODUCT FAMILY MODELS

SKU	Watts	Lumens	Lumens/Watt
LLS-X-HB9-240A-CC-[C]	150 200 240	22500 30000 36000	150
LLS-X-HB9-320A-CC-[C]	200 240 320	30000 36000 48000	150
LLS-X-HB9-150A-CC-[C]	80 100 150	12000 15000 22500	150

AMP DRAW

Watts	120V	Currei 240V	nt Amp Draw 277V	480V
80	0.67	0.33	0.29	0.17
100	0.83	0.42	0.36	0.21
150	1.25	0.63	0.54	0.31



Headquartered at: 1 Chestnut Street, 4M Nashua NH 03060